

Eaton 10NHG01B

Catalog Number: 10NHG01B

Fuse-link, LV, 10 A, AC 500 V, NH01, gL/gG, IEC, dual indicator, live gripping lugs



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage NH Fuse	10NHG01B
	UPC
	051712625890
EAN	Product Length/Depth
5027590428903	135 mm
Product Height	Product Width
57.8 mm	29.55 mm
Product Weight	Compliances
294.6666667 g	CE Marked
	RoHS Compliant
Certifications	
IEC 60269-1	
IEC 60269-2	
DIN 43620	

Type

fuse

Special features

Live gripping lug

Application

industrial

Utilities, Solar, Wind

Amperage Rating

10 A

Fitted with:

Metal gripping lugs

Fuse size

NH01

Current type

AC

Breaking capacity

120 kA

Frequency rating - max

62 Hz

Frequency rating - min

45 Hz

Rated switching capacity

120 kA

Rated voltage AC

500 V

Class

Class gG/gL

Fuse type

Square body with knife blade contact

Utilization category

gL/gG (cable protection/equipment protection)

Interrupt rating

120 kAIC

Fuse indicator

Combination fuse status indicator

Catalogs

CA134002EN

[eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf](#)

[NH Fuse links, bases and gear](#)

[Bussmann series complete full line catalog no. 1007](#)

Compliance information

[UKCA NH Size 01/1, 500V fuse-links](#)

[CE NH Size 01/1, 500V fuse-links](#)

Multimedia

[Eaton Bussmann – NH fuse link portfolio](#)

Presentations

[NH Overview Video](#)

Technical data sheets

[10164 NH 500 Volts gG](#)

Insulated metal gripping lugs (IMGL)

No

Connection

Blade end

Construction

NH01

Construction size

NH01

Fuse shape

Square body

Knife blade contacts

Voltage type

AC

Suitable for

Microswitch 170H0235

Material

Ceramic body

Quantity

3

Voltage rating

500 V



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.
All other trademarks are property of their respective owners.



Eaton.com/socialmedia