

Eaton 125NHG00B

Catalog Number: 125NHG00B

Eaton Bussmann series low voltage NH Fuse, Live gripping lug, 500V, 125A, 120 kAIC, Combination fuse status indicator, Blade end connection, Class C gL/gG, Square-body with knife blade contact, Metal plated copper contact plate

General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage NH Fuse	125NHG00B
	Model Code
	NH FUSE 125A 500V GG/GL SIZE 00
UPC	EAN
051712625876	5027590429894
Product Length/Depth	Product Height
79 mm	58 mm
Product Width	Product Weight
30 mm	182 g
Compliances	Certifications
CE Marked	IEC 60269-1
RoHS Compliant	IEC 60269-2
	DIN 43620



defaultTaxonomyAttributeLabel

Type

fuse

Special features

Live gripping lug

Application

industrial

Utilities, Solar, Wind

Amperage Rating

125 A

Fitted with:

Metal gripping lugs

Fuse size

NH02

Current type

AC

Breaking capacity

120 kA

Frequency rating - max

62 Hz

Frequency rating - min

45 Hz

Rated switching capacity

120 kA

Rated voltage AC

500 V

Class

Class gG/gL

Fuse type

Square body with knife blade contact

Contact material

Metal plated copper

Utilization category

gL/gG (cable protection/equipment protection)

Interrupt rating

Resources

Catalogs

NH Fuse links, bases and gear

[eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf](#)

[CA134002EN](#)

[Bussmann series complete full line catalog no. 1007](#)

Compliance information

[UKCA Size 00 NH 500V](#)

[125NHG00B~NH FUSE 125A 500V GG/GL SIZE 00](#)

Multimedia

[Eaton Bussmann – NH fuse link portfolio](#)

Presentations

[NH Overview Video](#)

Technical data sheets

[10164 NH 500 Volts gG](#)

120 kAIC

Fuse indicator

Combination fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Connection

Blade end

Construction

NH00

Construction size

NH00

Fuse shape

Square body

Knife blade contacts

Voltage type

AC

Suitable for

Microswitch BVL50

Material

Ceramic body

Metal gripping lugs

Quantity

3

Voltage rating

500 V