

Eaton 15KB6

Catalog Number: 15KB6

Expulsion fuse-link, medium voltage, 6 A, AC 15 kV, 533 mm, ANSI, K fast, style B termination



General specifications

Product Name	Catalog Number
Eaton Bussmann series medium voltage expulsion fuse	15KB6
	Model Code
	15KV 6A EXPULSION LINK
UPC	EAN
051712534123	5027590435307
Product Length/Depth	Product Height
225 mm	76 mm
Product Width	Product Weight
106 mm	18.96 g
Compliances	
ANSI C37.42	

[Type](#)

Medium Voltage Expulsion Fuse Link

[Application](#)

Primary side transformer protection, feeder protection, capacitor bank protection

[Amperage Rating](#)

6 A

[Current characteristic type](#)

Type K - Complies with ANSI C 37-42 requirements for fast acting K Characteristics

[Rated frequency - max](#)

60 Hz

[Rated frequency - min](#)

50 Hz

[Release characteristic](#)

K

[Standard](#)

ANSI

[Type of termination](#)

Fixed buttonhead

[Voltage type](#)

AC

[Color](#)

Yellow

[Interrupt rating](#)

8 kAIC

[Construction size](#)

533 mm

[Voltage rating](#)

15 kV

[Technical service bulletins](#)

[Datasheet - 15KB6](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)