

Eaton 15KBR15

Catalog Number: 15KBR15

Expulsion fuse-link, medium voltage, 15 A, AC 15 kV, 533 mm, ANSI, K fast, style BR termination

General specifications



Product Name	Catalog Number
Eaton Bussmann series medium voltage expulsion fuse	15KBR15
	Model Code
	15KV 15A REMOVABLE B/HEAD EXPULSION LINK
UPC	EAN
051712516792	5027590435413
Product Length/Depth	Product Height
106 mm	76 mm
Product Width	Product Weight
225 mm	34.76 g
Compliances	
ANSI C37.42	

Type

Medium Voltage Expulsion Fuse Link

Application

Primary side transformer protection, feeder protection, capacitor bank protection

Amperage Rating

15 A

Current characteristic type

Type K - Complies with ANSI C 37-42 requirements for fast acting K Characteristics

Rated frequency - max

60 Hz

Rated frequency - min

50 Hz

Release characteristic

K

Standard

ANSI

Type of termination

Removable buttonhead

Voltage type

AC

Color

Yellow

Interrupt rating

8 kAIC

Construction size

533 mm

Voltage rating

15 kV

Technical service bulletins

Datasheet - 15KBR15



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)