

Eaton 15XABR3

Catalog Number: 15XABR3

Expulsion fuse-link, medium voltage, 3 A, AC 15 kV, 533 mm, ANSI, XA extra rapid, style BR termination

General specifications



Photo is representative

Product Name	Catalog Number
Eaton Bussmann series medium voltage expulsion fuse	15XABR3
	UPC
	051712494441
EAN	Product Length/Depth
5027590436809	225 mm
Product Height	Product Width
76 mm	106 mm
Product Weight	Certifications
25.16 g	ANSI/IEEE Std C37.42

Type

Medium Voltage Expulsion Fuse Link

Application

Primary side transformer protection, feeder protection, capacitor bank protection

Amperage Rating

3 A

Current characteristic type

Type XA - This type of expulsion fuse link has an extra rapid characteristic. It is suitable for applications where a high degree of system protection is required at the expense of discrimination.

Rated frequency - max

60 Hz

Rated frequency - min

50 Hz

Release characteristic

Other

Standard

ANSI

Type of termination

Removable buttonhead

Voltage type

AC

Color

Pink

Interrupt rating

8 kAIC

Construction size

533 mm

Voltage rating

15 kV



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)