

# Eaton 20D27

Catalog Number: 20D27

Eaton Bussmann series low voltage D fuse, 500V, 20A, 50 kAIC, Non Indicating, fuse, Class C gL/gG, Time delay, Blue, Ceramic body



## General specifications

| Product Name                             | Catalog Number       |
|------------------------------------------|----------------------|
| Eaton Bussmann series low voltage D fuse | 20D27                |
|                                          | UPC                  |
|                                          | 051712832335         |
| EAN                                      | Product Length/Depth |
| 5027590467759                            | 50 mm                |
| Product Height                           | Product Width        |
| 21.5 mm                                  | 21.5 mm              |
| Product Weight                           | Compliances          |
| 29.64 g                                  | CE Marked            |
|                                          | GoST-R               |
|                                          | RoHS Compliant       |
| Certifications                           |                      |
| IEC 60269                                |                      |
| VDE                                      |                      |
| DIN EN 60269-3 (VDE 0636 Part 30)        |                      |
| DIN EN 60269-1 (VDE 0636 Part 10)        |                      |
| DIN VDE 0636-301                         |                      |

## defaultTaxonomyAttributeLabel

### Type

fuse

### Application

For domestic and general industrial applications

### Amperage Rating

20 A

### Fuse size

DII

### Breaking capacity

50 kA

### Construction size (fuse inserts)

DII

### Rated voltage AC

500 V

### Class

Class C gL/gG

### Fuse type

D27 -Time delay

### Accessory/spare part type

20GD27 Blue screw cap gauge piece

### Utilization category

gL/gG (cable protection/equipment protection)

### Color

Blue

### Interrupt rating

50 kAIC

### Fuse indicator

Non-indicating

### Connection

Other

### Construction

D2

### Construction size

DII

### Fuse shape

## Resources

### Brochures

[eaton-bussmann-series-d-and-d0-fuses-product-aid-pa132014en-en-us.pdf](#)

### Catalogs

CA134002EN

[Bussmann series complete full line catalog no. 1007](#)

[20D27~Eaton Bussmann series low voltage D fuse](#)

### Compliance information

[UKCA Bottle fuse-links, holders, carriers and accessories](#)

[CE Bottle fuse-links, holders, carriers and accessories](#)

### Sales notes

[Product change notification PCN\\_BUR\\_00188](#)

### Technical data sheets

[4124 D and D0 fuses, bases and accessories](#)

Bottle

Response time

Time-delay

Suitable for

- E27/DII Fuse base
- TFD27 Fuse base screw fixing
- SFRD27 Fuse base DIN-Rail mount
- TFRD27 Fuse base DIN-Rail mount

Material

White ceramic body

Release characteristic

Time-lag

Quantity

25

Voltage rating

500 V



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.  
All other trademarks are property of their respective owners.



Eaton.com/socialmedia