

Eaton 24OEGMA50

Catalog Number: 24OEGMA50

Oil fuse-link, medium voltage, 50 A, AC 24 kV, BS2692 F02, 359 x 63.5 mm, back-up, BS, IEC, ESI, with striker

General specifications



Product Name	Catalog Number
Eaton Bussmann series medium voltage oil fuse	24OEGMA50
	UPC
	051712585712
EAN	Product Length/Depth
5027590469128	359 mm
Product Height	Product Width
63.5 mm	63.5 mm
Product Weight	Warranty
2600 g	Not Applicable
Compliances	Certifications
BS 2692-1	IEC Rated
ESI 12-8	IEC60282-1

Type

fuse

Application

protection of primary side transformer, and oil-filled fuse switch
combination unit

Amperage Rating

50 A

Fuse indicator

with striker

Fuse size

63.5 x 359 mm

Breaking capacity

25 kA

Installation technique

Oil

Performance Cat According To IEC 60282-1

Back-up

Product application

Primary side transformer protection

Rated frequency - max

60 Hz

Rated frequency - min

50 Hz

Release characteristic

Other

Standard

British Standard

Utilization category

Other

Voltage type

AC

With striker

Yes

Fuse diameter

63.5 mm

Joule integral (I²T) - max operating

2.4 x 10⁴

Joule integral (I²T) - min pre-arcing

1.2 x 10³

Resistance

34

Class

Class back-up

Barrels

1

Construction type

F02/BS 2692

Fuse shape

Cylindrical

Interrupt rating

25 kAIC

Construction size

63.5 x 359 mm

Voltage rating

24 kV

Fuse type

OEGM



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia