

Eaton 250NHG2B-690

Catalog Number: 250NHG2B-690

Eaton Bussmann series low voltage NH Fuse, Live gripping lug, 690V, 250A, 120 kAIC, Combination fuse status indicator, fuse, Blade end connection, Class C gL/gG, Square-body with knife blade contact, Ceramic body



General specifications

Product Name

Eaton Bussmann series low voltage NH Fuse

Catalog Number

250NHG2B-690

Model Code

NH FUSE 250A 690V gG SIZE 2

UPC

051712191173

EAN

5027590469753

Product Length/Depth

150 mm

Product Height

71 mm

Product Width

54 mm

Product Weight

651 g

Warranty

Not Applicable

Compliances

RoHS Compliant
CE Marked

Certifications

IEC 60269-1
IEC 60269-2
DIN 43620

Product specifications

Interrupt rating

120 kAIC

Accessory/spare part type

SDL-2 Solid link

FEH- Fuse extraction handle

SD12-SK Shroud kit

SD12-PB 2-phase barriers and 2 ganging links

TD2-IP20 Triple pole protection kit

Insulated metal gripping lugs (IMGL)

No

Current type

AC

Suitable for

SD2-D Single pole NH Fuse base

TD2-D Tripe pole NH Fuse base

Microswitch 170H0235

Microswitch 170H0236

EBH Size 00 to 4 Horizontal fuse switch-disconnectors

Amperage Rating

250 A

Frequency rating - max

62 Hz

Fuse type

Square body with knife blade contact

Fitted with:

Metal gripping lugs

Rated switching capacity

120 kA

Fuse size

NH2

Rated switching capacity AC

120 kA

Voltage rating

690 V

Fuse indicator

Combination fuse status indicator

Resources

Catalogs

NH Fuse links, bases and gear

Bussmann series complete full line catalog no. 1007

Compliance information

UKCA NH Size 2, 690V fuse-links

CE NH Size 2, 690V fuse-links

Presentations

NH Overview Video

Special features

Live gripping lug

Construction

NH2

Construction size

NH2

Rated voltage AC

690 V

Connection

Blade end

Quantity

3

Material

Ceramic body

Utilization category

gL/gG (cable protection/equipment protection)

Watt losses

23 W

Type

Fuse

Fuse shape

Square body

Knife blade contacts

Breaking capacity

120 kA

Frequency rating - min

45 Hz

Class

Class gG/gL

Application

industrial

Utilities, Solar, Wind

Voltage type

AC

Packaging type

Standard



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)