

Eaton 25KB40

Catalog Number: 25KB40

Expulsion fuse-link, medium voltage, 40 A, AC 25 kV, 660 mm, ANSI, K fast, style B termination



General specifications

Product Name	Catalog Number
Eaton Bussmann series medium voltage expulsion fuse	25KB40
	UPC
	051712398671
EAN	Product Length/Depth
5027590470308	225 mm
Product Height	Product Width
76 mm	106 mm
Product Weight	Certifications
44.04 g	ANSI/IEEE Std C37.42

Type

Medium Voltage Expulsion Fuse Link

Application

Primary side transformer protection, feeder protection, capacitor bank protection

Amperage Rating

40 A

Current characteristic type

Type K - Complies with ANSI C 37-42 requirements for fast acting K Characteristics

Rated frequency - max

60 Hz

Rated frequency - min

50 Hz

Release characteristic

K

Standard

ANSI

Type of termination

Fixed buttonhead

Voltage type

AC

Color

Yellow

Interrupt rating

8 kAIC

Construction size

660 mm

Voltage rating

25 kV



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



Eaton.com/socialmedia