

Eaton 25KBR6

Catalog Number: 25KBR6

Expulsion fuse-link, medium voltage, 6 A, AC 25 kV, 660 mm, ANSI, K fast, style BR termination



General specifications

Product Name	Catalog Number
Eaton Bussmann series medium voltage expulsion fuse	25KBR6
	Model Code
	25KV 6A REMOVABLE B/H EXPULSION LINK
UPC	EAN
051712296342	5027590470599
Product Length/Depth	Product Height
225 mm	76 mm
Product Width	Product Weight
106 mm	23.64 g
Compliances	
ANSI C37.42	

Type

Medium Voltage Expulsion Fuse Link

Application

Primary side transformer protection, feeder protection, capacitor bank protection

Amperage Rating

6 A

Current characteristic type

Type K - Complies with ANSI C 37-42 requirements for fast acting K Characteristics

Rated frequency - max

60 Hz

Rated frequency - min

50 Hz

Release characteristic

K

Standard

ANSI

Type of termination

Removable buttonhead

Voltage type

AC

Color

Yellow

Interrupt rating

8 kAIC

Construction size

660 mm

Voltage rating

25 kV

Technical service bulletins

Datasheet - 25KBR6



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)