

Eaton 40NHG000B-690

Catalog Number: 40NHG000B-690

Eaton Bussmann series low voltage NH Fuse, Live gripping lug, 690V, 40A, 120 kAIC, Combination fuse status indicator, fuse, Blade end connection, Class C gL/gG, Square-body with knife blade contact, Ceramic body

Product specifications

Interrupt rating	Insulated metal gripping lugs (IMGL)
120 kAIC	No
Current type	Suitable for
AC	Microswitch 170H0236
	EBF Vertical fuse rail
	EBV Vertical fuse switch-disconnectors
	EBH Size 000 Horizontal fuse switch-disconnectors
Amperage Rating	Frequency rating - max
40 A	62 Hz
Fuse type	Fitted with:
Square body with knife blade contact	Metal gripping lugs
Rated switching capacity	Fuse size
120 kA	NH000
Rated switching capacity AC	Voltage rating
120 kA	690 V
Fuse indicator	Special features
Combination fuse status indicator	Live gripping lug
Construction	Construction size
NH000	NH000
690 V	Blade end

Resources	Rated voltage AC	Connection
	Quantity	Material
		Ceramic body
	Utilization category	Watt losses
	gL/gG (cable protection/equipment protection)	4 W
Catalogs		Type
NH Fuse links, bases and gear		Fuse
Bussmann series complete full line catalog no. 1007		Breaking capacity
Compliance information	Fuse shape	120 kA
UKCA NH Size 000, 690V fuse-links	Knife blade contacts	Frequency rating - min
CE NH Size 000, 690V fuse-links	Square body	45 Hz
Presentations	Class	Application
NH Overview Video	Class gG/gL	Voltage type
		AC
	Packaging type	
	Standard	



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.
All other trademarks are property of their respective owners.



Eaton.com/socialmedia