

Eaton BC63M100

Catalog Number: BC63M100

Fuse-link, low voltage, 63A, AC 500 V, BS88, 21 x 114 mm, gM, BS, 63M100



Photo is representative

General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage british standard fuse	BC63M100
	UPC
	051712578479
EAN	Product Length/Depth
5027590492140	3.302 mm
Product Height	Product Width
21.082 mm	113.538 mm
Product Weight	Warranty
60.5 g	Not Applicable
Compliances	Certifications
CE Marked	IEC 60269-2
RoHS Compliant	BS88

Type

Fuse

Application

general industrial applications

Amperage Rating

63 A

Fitted with:

Centre bolted tags

Current type

AC/DC

Mounting dimension

M6

Center-to-center distance of connections

97.5 mm

Breaking capacity

80 kA

Rated switching capacity

80 kA

Motor current rating

63M100

Rated voltage AC

500 V

Rated voltage DC

250 V

Class

Class gM

Fuse type

BC

Utilization category

gM (motor protection)

Color

None

Interrupt rating

80 kAIC

Fuse indicator

Catalogs

[CA134002EN](#)[BC63M100~Eaton Bussmann series low voltage British standard fuse](#)[Bussmann series complete full line catalog no. 1007](#)

Multimedia

[Eaton Bussmann - Red Spot fuse links](#)

Technical data sheets

[4113 BC fuses](#)

None

Insulated metal gripping lugs (IMGL)

No

Watt losses

3.4 W

Connection

97 mm fixing centre

Construction

BS88

Construction size

Other

Fuse shape

Center bolted tags

Voltage type

AC

AC/DC

Voltage rating

500 V

Fuse system (according to IEC 60269)

Other



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.
All other trademarks are property of their respective owners.



Eaton.com/socialmedia