

Eaton BC63M80

Catalog Number: BC63M80

Eaton Fuse-link, low voltage, 63A, AC 500 V, BS88, 21 x 114 mm, gM, BS, 63M80



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage british standard fuse	BC63M80
	UPC
	051712578486
EAN	Product Length/Depth
5027590492157	114 mm
Product Height	Product Width
21 mm	21 mm
Product Weight	Warranty
58.5 g	Not Applicable
Compliances	Certifications
CE Marked	IEC 60269-2
RoHS Compliant	BS88

defaultTaxonomyAttributeLabel

Type

Fuse

Application

general industrial applications

Amperage Rating

80 A

Fitted with:

Centre bolted tags

Current type

AC/DC

Mounting dimension

M6

Center-to-center distance of connections

97.5 mm

Breaking capacity

80 kA

Rated switching capacity

80 kA

Motor current rating

63M80

Rated voltage AC

500 V

Rated voltage DC

250 V

Class

Class gM

Fuse type

BC

Utilization category

gM (motor protection)

Color

None

Interrupt rating

80 kAIC

Fuse indicator

Resources

Catalogs

CA134002EN

BC63M80~63M80 500V AC INDUSTRIAL

Bussmann series complete full line catalog no. 1007

Multimedia

Eaton Bussmann - Red Spot fuse links

Technical data sheets

4113 BC fuses

None

Insulated metal gripping lugs (IMGL)

No

Watt losses

4.4 W

Connection

97 mm fixing centre

Construction

BS88

Construction size

Other

Fuse shape

Center bolted tags

Voltage type

AC

AC/DC

Voltage rating

500 V

Fuse system (according to IEC 60269)

Other



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.
All other trademarks are property of their respective owners.



Eaton.com/socialmedia