

Eaton BD63

Catalog Number: BD63

Eaton Fuse-link, LV, 63 A, AC 500 V, BS88, 21 x 129 mm, gL/gG, BS



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage british standard fuse	BD63
	UPC
	051712838603
EAN	Product Length/Depth
5027590492188	129 mm
Product Height	Product Width
21 mm	21 mm
Product Weight	Warranty
66.9 g	Not Applicable
Compliances	Certifications
CE Marked	IEC 60269-2
RoHS Compliant	BS88

Type

Fuse

Application

general industrial applications

Amperage Rating

63 A

Fitted with:

Centre bolted tags

Current type

AC/DC

Mounting dimension

M8

Center-to-center distance of connections

111 mm

Breaking capacity

80 kA

Rated switching capacity

80 kA

Rated voltage AC

500 V

Rated voltage DC

250 V

Class

Class gG/gL

Fuse type

BD

Utilization category

gG (cable protection/equipment protection)

Color

None

Interrupt rating

80 kAIC

Fuse indicator

None

Insulated metal gripping lugs (IMGL)

Catalogs

CA134002EN

Bussmann series complete full line catalog no. 1007

Compliance information

CE AC*, BC*, AD*, BD* fuse-links

UKCA AC*, BC*, AD*, BD* fuse-links

Multimedia

Eaton Bussmann - Red Spot fuse links

Technical data sheets

4114 BD fuses

No

Watt losses

5.6 W

Connection

111 mm fixing centre

Construction

BS88

Construction size

Other

Fuse shape

Center bolted tags

Voltage type

AC

AC/DC

Voltage rating

500 V

Fuse system (according to IEC 60269)

Other



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



Eaton.com/socialmedia