


STAINLESS STEEL FLEXIBLE CONDUIT (Type 316SS)

Coated Flex Conduit 25' Length			NEMA4X		Suitable for damp locations	
Trade Size	Metric Size	Outside Dia.	Inside Dia.	Bend	Wt. 25' Coil (lbs)	Part Number
½"	16	0.840"	0.610"	4-½"	5.50	S60500CTFC
¾"	21	1.050"	0.790"	6"	7.00	S60700CTFC
1"	27	1.315"	1.010"	10"	9.00	S61000CTFC
1-¼"	35	1.660"	1.330"	11"	11.00	S61200CTFC
1-½"	41	1.900"	1.520"	12"	12.00	S61500CTFC
2"	53	2.370"	2.060"	14"	20.00	S62000CTFC

Clear Coated Flex Conduit 25' Length			NEMA4X		Suitable for damp locations	
Trade Size	Metric Size	Outside Dia.	Inside Dia.	Bend	Wt. 25' Coil (lbs)	Part Number
½"	16	0.840"	0.610"	4-½"	5.50	S60500CTCC
¾"	21	1.050"	0.790"	6"	7.00	S60700CTCC
1"	27	1.315"	1.010"	10"	9.00	S61000CTCC
1-¼"	35	1.660"	1.330"	11"	11.00	S61200CTCC
1-½"	41	1.900"	1.520"	12"	12.00	S61500CTCC
2"	53	2.370"	2.060"	14"	20.00	S62000CTCC


Bare Flex Conduit 25' Length			NEMA4X		Suitable for damp locations	
Trade Size	Metric Size	Outside Dia.	Inside Dia.	Bend	Wt. 25' Coil (lbs)	Part Number
½"	16	0.744"	0.610"	4"	4.50	S60500CTFX
¾"	21	0.960"	0.790"	4-½"	5.50	S60700CTFX
1"	27	1.160"	1.010"	6"	7.00	S61000CTFX
1-¼"	35	1.500"	1.330"	7-½"	8.50	S61200CTFX
1-½"	41	1.750"	1.520"	9"	10.00	S61500CTFX
2"	53	2.125"	2.020"	10"	13.00	S62000CTFX



STAINLESS STEEL FLEXIBLE CONNECTORS (Type 316SS)

Flex Connector Male 90° Elbow			NEMA4X		Suitable for damp locations	
Trade Size	Metric Size	Wt. (lbs)	A	B	C	Part Number
½"	16	0.27	1.950"	1.250"	2.150"	S60500FC90
¾"	21	0.50	2.250"	1.540"	2.630"	S60700FC90
1"	27	0.72	2.800"	1.860"	3.000"	S61000FC90
1-¼"	35	0.95	3.150"	2.250"	3.150"	S61200FC90
1-½"	41	1.55	3.750"	2.580"	3.750"	S61500FC90
2"	53	2.35	4.450"	3.050"	4.750"	S62000FC90

Flex Connector Male Straight			NEMA4X		Suitable for damp locations	
Trade Size	Metric Size	Wt. (lbs)	A	B	Part Number	
½"	16	0.17	1.530"	1.250"	S60500FCS0	
¾"	21	0.24	1.580"	1.540"	S60700FCS0	
1"	27	0.33	1.800"	1.650"	S61000FCS0	
1-¼"	35	0.58	2.000"	2.250"	S61200FCS0	
1-½"	41	0.85	2.175"	2.650"	S61500FCS0	
2"	53	1.19	2.350"	3.210"	S62000FCS0	



*45° Flex Connectors available in ½", ¾" and 1"