

## STAINLESS STEEL RIGID CONDUIT

|            |             | Diameters |        |         | 10' Length w/ Coupling |            | 5' Length w/ Coupling |            |
|------------|-------------|-----------|--------|---------|------------------------|------------|-----------------------|------------|
| Trade Size | Metric Size | OD        | ID     | Wt./Ft. | Type 304               | Type 316   | Type 304              | Type 316   |
| ½"         | 16          | 0.840"    | 0.622" | 0.82    | S40510CT00             | S60510CT00 | S40505CT00            | S60505CT00 |
| ¾"         | 21          | 1.050"    | 0.824" | 1.09    | S40710CT00             | S60710CT00 | S40705CT00            | S60705CT00 |
| 1"         | 27          | 1.315"    | 1.049" | 1.61    | S41010CT00             | S61010CT00 | S41005CT00            | S61005CT00 |
| 1-¼"       | 35          | 1.660"    | 1.380" | 2.18    | S41210CT00             | S61210CT00 | S41205CT00            | S61205CT00 |
| 1-½"       | 41          | 1.900"    | 1.610" | 2.63    | S41510CT00             | S61510CT00 | S41505CT00            | S61505CT00 |
| 2"         | 53          | 2.375"    | 2.067" | 3.50    | S42010CT00             | S62010CT00 | S42005CT00            | S62005CT00 |
| 2-½"       | 63          | 2.875"    | 2.469" | 5.59    | S42510CT00             | S62510CT00 | S42505CT00            | S62505CT00 |
| 3"         | 78          | 3.500"    | 3.068" | 7.27    | S43010CT00             | S63010CT00 | S43005CT00            | S63005CT00 |
| 4"         | 103         | 4.500"    | 4.026" | 10.08   | S44010CT00             | S64010CT00 | S44005CT00            | S64005CT00 |
| 5"         | 129         | 5.563"    | 5.073" | 14.61   | S45010CT00             | S65010CT00 | S45005CT00            | S65005CT00 |
| 6"         | 155         | 6.625"    | 6.093" | 18.97   | S46010CT00             | S66010CT00 | S46005CT00            | S66005CT00 |



Calbrite™ stainless steel rigid conduit is manufactured in type 304 and 316 stainless to meet stringent sanitary requirements and withstand harsh corrosive environments. The conduit is polished to a bright, easily maintainable finish that allows for minimal cleaning, enhances the appearance, and improves the surface's resistance to pitting & bacterial corrosion in CIP (clean-in-place) and SIP (sterilize-in-place) systems.

Calbrite stainless steel rigid conduit is highly resistant to damage from impact. Easy to cut, form and join, stainless steel conduit avoids the labor-intensive procedures that come with PVC-coated installation. No special tools or complicated maintenance and repair procedures are required. In addition to the ease of installation and maintenance, stainless steel is 100% recyclable. Standard rigid conduit threads allow for trouble-free installations.

\* Trade sizes ½" to 6"

\* Includes one coupling with each length purchased

\* Custom lengths and diameters are available

\* Conduit is domestically manufactured in our USA manufacturing facilities

Compliances: Underwriter Laboratories Listed for

USA and Canada standard UL6A File # E230584

American National Standards Institute (ANSI) specification C80.1

## STAINLESS STEEL RIGID NIPPLES Custom lengths available upon request



| Type 304 SS |            |  |            |            |            |            |            |            |            |
|-------------|------------|-------------------------------------------------------------------------------------|------------|------------|------------|------------|------------|------------|------------|
| Trade Size  | Close      | 1-½"                                                                                | 2"         | 2-½"       | 3"         | 3-½"       | 4"         | 5"         | 6"         |
| ½"          | S405CLCN00 | S40515CN00                                                                          | S40520CN00 | S40525CN00 | S40530CN00 | S40535CN00 | S40540CN00 | S40550CN00 | S40560CN00 |
| ¾"          | S407CLCN00 | S40715CN00                                                                          | S40720CN00 | S40725CN00 | S40730CN00 | S40735CN00 | S40740CN00 | S40750CN00 | S40760CN00 |
| 1"          | S410CLCN00 |                                                                                     | S41020CN00 | S41025CN00 | S41030CN00 | S41035CN00 | S41040CN00 | S41050CN00 | S41060CN00 |
| 1-¼"        | S412CLCN00 |                                                                                     | S41220CN00 | S41225CN00 | S41230CN00 | S41235CN00 | S41240CN00 | S41250CN00 | S41260CN00 |
| 1-½"        | S415CLCN00 |                                                                                     | S41520CN00 | S41525CN00 | S41530CN00 | S41535CN00 | S41540CN00 | S41550CN00 | S41560CN00 |
| 2"          | S420CLCN00 |                                                                                     |            |            | S42030CN00 | S42035CN00 | S42040CN00 | S42050CN00 | S42060CN00 |
| 2-½"        | S425CLCN00 |                                                                                     |            |            |            |            |            | S42550CN00 | S42560CN00 |
| 3"          | S430CLCN00 |                                                                                     |            |            |            |            |            | S43050CN00 | S43060CN00 |
| 4"          | S440CLCN00 |                                                                                     |            |            |            |            |            | S44050CN00 | S44060CN00 |

| Type 316 SS |            |  |            |            |            |            |            |            |            |
|-------------|------------|-------------------------------------------------------------------------------------|------------|------------|------------|------------|------------|------------|------------|
| Trade Size  | Close      | 1-½"                                                                                | 2"         | 2-½"       | 3"         | 3-½"       | 4"         | 5"         | 6"         |
| ½"          | S605CLCN00 | S60515CN00                                                                          | S60520CN00 | S60525CN00 | S60530CN00 | S60535CN00 | S60540CN00 | S60550CN00 | S60560CN00 |
| ¾"          | S607CLCN00 | S60715CN00                                                                          | S60720CN00 | S60725CN00 | S60730CN00 | S60735CN00 | S60740CN00 | S60750CN00 | S60760CN00 |
| 1"          | S610CLCN00 |                                                                                     | S61020CN00 | S61025CN00 | S61030CN00 | S61035CN00 | S61040CN00 | S61050CN00 | S61060CN00 |
| 1-¼"        | S612CLCN00 |                                                                                     | S61220CN00 | S61225CN00 | S61230CN00 | S61235CN00 | S61240CN00 | S61250CN00 | S61260CN00 |
| 1-½"        | S615CLCN00 |                                                                                     | S61520CN00 | S61525CN00 | S61530CN00 | S61535CN00 | S61540CN00 | S61550CN00 | S61560CN00 |
| 2"          | S620CLCN00 |                                                                                     |            |            | S62030CN00 | S62035CN00 | S62040CN00 | S62050CN00 | S62060CN00 |
| 2-½"        | S625CLCN00 |                                                                                     |            |            |            |            |            | S62550CN00 | S62560CN00 |
| 3"          | S630CLCN00 |                                                                                     |            |            |            |            |            | S63050CN00 | S63060CN00 |
| 4"          | S640CLCN00 |                                                                                     |            |            |            |            |            | S64050CN00 | S64060CN00 |

\* Contact factory for 5" and 6" Conduit Nipple info.