

Carlon®

Liquidtight Flexible Non-Metallic Conduit & Fittings

T&B Catalog Number:

LT20F-NEW

UPC Number:

03448119417

Status:

Active

Description:

1 Inch, 90 Degree, Two-Piece Liquidtight Non-Metallic Fitting, UL E32447, Temperatures up to 107 Degrees C, Nitril Rubber O-Ring, PVC, Grey

Features

- Non-conductive and non-corrosive.
- Resistant to oil, acid, ozone and alkaline.
- Easy to install.
- Approved for indoor and outdoor locations
- UL listed for wet locations
- Nitrile rubber 'O' ring for a liquidtight termination.
- Temperatures up to 225 degree F (107 degree C)
- Meets UL standard 514B.

Application

For use with Carflex conduit and Carflex X-Flex conduit.

General

Trade Size (inches)	1
Material	Non-Metallic

Dimension Information

Size (inches)	1
Degree of Bend	90
A (inches)	0.7
B (inches)	2.01
C (inches)	2.01
D (inches)	2.26
E (inches)	2.04
F (inches)	1.9

Packaging

T&B Order Multiple	25
Package in Units	25
T&B Sold in UOM	Each
T&B Weight Per UOM	23.5 lbs. per 100

Application Support

T&B Sales Drawings	wsd-ac01708
Product Overview-Carflex Liquidtight Flex-Available on Website	
ible Tubing	

Certifications

RoHS Compliance	Yes
-----------------	-----

