



Representative

**Catalog Number:** H200-TB  
**Product ID:** 7TBD013770R0003  
**UPC Number:** 78621050405  
**EAN Number:** 05414363152446  
**Status:** Active

2 Inch Zinc Hub Connector with Thermoplastic Insulating Throat, Sealing Ring Nitrile (BUNA-N) for Use with Rigid/IMC Conduit

- Suitable for hazardous locations use in Class II, Groups E, F, G & Class III locations per CEC 18-202; 18-252; 18-302; 18-352.

#### Header

3D Model Available on Website

#### North American Specifications (UNSPSC)

|                    |                                                                                 |
|--------------------|---------------------------------------------------------------------------------|
| UNSPSC             | 39121311 Electrical fittings                                                    |
| IGCC               | 4441 Electrical fittings                                                        |
| Brand Name         | T&B                                                                             |
| Type               | Hub Connector                                                                   |
| Special Features   | Sealing Ring and Groove with Innovative Profile Better Than Standard O-Ring     |
| Application        | To Connect Threaded Metal Conduit to a Threadless Opening in a Box or Enclosure |
| Standard           | UL E23018, CSA                                                                  |
| Size               | 2 Inch                                                                          |
| Material           | Zinc                                                                            |
| Temperature Rating | 105 Degrees C                                                                   |

#### European Specifications (ETIM)

|                                                     |                                                        |
|-----------------------------------------------------|--------------------------------------------------------|
| ETIM                                                | EC001180 Screw connection for protective metallic hose |
| Nominal size in inch                                | 2 inch                                                 |
| Model                                               | Straight                                               |
| Revolving thread                                    | N                                                      |
| Connection type screw connection to housing         | Thread                                                 |
| Thread type                                         | NPT                                                    |
| Material housing                                    | Zinc die-cast                                          |
| Approved in combination with protective conduit CSA | Y                                                      |
| Approved in combination with protective conduit UL  | Y                                                      |
| Operating temperature                               | 0-+105°C                                               |

#### Packaging

|                           |                |
|---------------------------|----------------|
| Outer Quantity            | 5              |
| Outer Dimensions (inches) | 8.1x4x6.9      |
| Weight Uom                | 1.02 lbs. Each |

#### Documents / Support Tools

|                         |                      |
|-------------------------|----------------------|
| Technical Data Sheet US | Available on Website |
| Technical Data Sheet CA | Available on Website |

For further technical assistance, please contact us...

Thomas & Betts - USA  
 8155 T&B Blvd.  
 Memphis, TN 38125  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
 MS 3B-50  
 8155 T&B Blvd.  
 Memphis, TN 38125

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321

