

BAF

Description:

Fast-acting, supplemental fuse.

For superior protection, Eaton recommends upgrading to Bussmann series Low-Peak™ Class CC fuses. See data sheet # 1023.

Catalog symbol – color code:

- BAF - Green (250Vac max 1/4 to 30A)

Ratings:

Fuse amp range	Interrupting rating at system voltage		Agency information	
	250 Vac	125 Vac	UL	CSA
1/4 to 1	35A	10kA	-	X
1-1/2 to 2-1/2	100A	10kA	-	X
3	100A	10kA	X	X
4 to 10	200A	10kA	X	X
12 to 15	750A	10kA	X	X
20 to 30	200A	10kA	-	-

Agency information:

- CE
- UL Listed, Std. 248-14, 250Vac (3 to 15A) Guide JDYX, File E19180
- CSA Certified, 250Vac (1/4 to 15A) Class 1422-01, File 53787

Catalog numbers (amps)

BAF-1/4	BAF-1-8/10	BAF-6	BAF-12
BAF-1/2	BAF-2	BAF-6-1/4	BAF-15
BAF-6/10	BAF-2-1/2	BAF-7	BAF-20
BAF-8/10	BAF-3	BAF-8	BAF-25
BAF-1	BAF-4	BAF-9	BAF-30
BAF-1-1/2	BAF-5	BAF-10	

Features:

- Color coded green for 250Vac maximum voltage rating
- Fiber tube construction
- Nickel-plated brass endcaps.

Typical applications:

- General purpose circuits
- Lighting circuit protection
- Meter circuits

For superior electrical protection, Eaton recommends upgrading BAF fuse applications to Bussmann series Low-Peak LP-CC fuses See page 1-7.

Data Sheet: 2011 (0-30)



KTk

Description:

Fast-acting supplemental fuse.

For superior protection, Eaton recommends upgrading to Bussmann series Low-Peak™ Class CC fuses. See data sheet # 1023.

Catalog symbol / color code:

- KTK - Black (600Vac maximum voltage)

Ratings:

Fuse amp range	Interrupting rating at rated voltage	Agency information	
	600Vac	UL	CSA
1/10 to 30	100kA	X	X

Agency information:

- CE, RoHS compliant
- UL Listed, Std. 248-14, Guide JDYX, File E19180
- CSA Certified: C22.2 No. 248.14, Class 1422-01, File 53787, HRC-MISC

RoHS

Catalog numbers (amps)

KTk-1/10	KTk-3/4	KTk-4	KTk-12
KTk-1/8	KTk-1	KTk-5	KTk-15
KTk-2/10	KTk-1-1/4	KTk-6	KTk-20
KTk-1/4	KTk-1-1/2	KTk-7	KTk-25
KTk-3/10	KTk-2	KTk-7-1/2	KTk-30
KTk-4/10	KTk-2-1/2	KTk-8	
KTk-1/2	KTk-3	KTk-9	
KTk-6/10	KTk-3-1/2	KTk-10	

Features:

- Color coded black for 600Vac voltage rating
- Fast-acting for resistive loads
- Melamine tube construction
- Nickel-plated bronze endcaps

Typical applications:

- Control circuits
- Lighting circuit protection
- Meter circuits

For superior electrical protection, Eaton recommends upgrading KTK fuse applications to Bussmann series Low-Peak LP-CC fuses See page 1-7.

Data Sheet: 1011



Recommended fuse blocks/fuse holders for 13/32" x 1 1/2" fuses

- See page 3-2