

KLM**Description:**

Fast-acting supplemental fuse.

For superior protection, Eaton recommends upgrading to Bussmann series Low-Peak™ Class CC fuses. See data sheet # 1023.

For protecting DC photovoltaic systems, Eaton recommends using Bussmann series PVM 10x30mm PV fuses. See data sheet # 10121.

Catalog symbol / color code:

- KLM - Black (600Vac/dc maximum voltage)


Ratings:

Fuse amp range	Interrupting rating at rated voltage		Agency information	
	600 Vac	600 Vdc	UL	CSA
1/10 to 30	100kA	50kA	X	X

Electrical characteristics:

% of amp rating	Opening time
110%	4 Hours minimum
135%	AC Opens within 1 hour

Agency information:

- CE, RoHS compliant
- UL Listed: Std. 248-14, Guide JDYX, File E19180
- CSA Certified, C22.2 No. 248. 14, Class 1422-01, File 53787

Catalog numbers (amps)

KLM-1/10	KLM-1	KLM-5	KLM-15
KLM-1/8	KLM-1-1/4	KLM-6	KLM-20
KLM-2/10	KLM-1-1/2	KLM-7	KLM-25
KLM-1/4	KLM-2	KLM-8	KLM-30
KLM-3/10	KLM-2-1/2	KLM-9	
KLM-1/2	KLM-3	KLM-10	
KLM-3/4	KLM-4	KLM-12	

Features:

- Color coded for 600Vac/dc
- A full range DC supplemental fuse
- Melamine tube construction
- Nickel-plated brass endcaps.

Recommended fuse blocks/fuse holders for 13/32" x 1 1/2" fuses

- See page 3-2

Data Sheet: 2020