

Industrial grade plugs & connectors

Industrial grade plugs & connectors quick reference guide

AMP	V/AC	NEMA	Grip	Special	Body	Color	Page	Plug	Connector
15	125	 5-15P 5-15R	ULTRA		STR	BK & W	B-10	AH5266	AH5269
					STR	BK	B-10	AH5266BK	AH5269BK
				HG	STR	BK & W	B-8	AH8215HG	AH8219HG
			SAFETY		ANG	BK & W	B-10	AH5266A	—
				HG	ANG	BK & W	B-8	AH8215HGA	—
				HG	ANG	C	B-8	AH8215HGAC	—
				HG	STR	C	B-8	AH8215HGC	AH8219HGC
			QUICK		STR	BK	B-10	AH5965BK	AH5969BK
					STR	Y	B-10	AH5965Y	AH5969Y
				HG	STR	W	B-8	AH8115W	AH8119W
			AUTO		STR	BK & W	B-10	5266N	5269N
				HG	STR	BK & W	B-8	5266NHG	5269NHG
20	125	 5-20P 5-20R	ULTRA		STR	BK & W	B-11	AH5366	AH5369
				HG	STR	BK & W	B-8	AH8315HG	AH8319HG
			SAFETY	HG	ANG	BK & W	B-8	AH8315HGA	—
				HG	ANG	C	B-8	AH8315HGAC	—
			QUICK		STR	BK	B-11	AH5364BK	AH5369BK
					STR	Y	B-11	AH5364Y	AH5369Y
				HG	STR	BK & W	B-8	5366NHG	5369NHG
15	250	 6-15P 6-15R	ULTRA		STR	BK & W	B-11	AH5666	AH5669
				HG	ANG	BK & W	B-9	AH8225HGA	—
			SAFETY	HG	ANG	C	B-9	AH8225HGAC	—
					STR	BK	B-11	AH5666BK	AH5669BK
			QUICK		STR	Y	B-11	AH5666Y	AH5669Y
					STR	BK & W	B-11	5666N	5669N
			AUTO		STR	BK & W	B-11	5666N	5669N
20	250	 6-20P 6-20R	ULTRA		STR	BK & W	B-12	AH5466	AH5469
				HG	ANG	BK & W	B-9	AH8325HGA	—
			SAFETY	HG	ANG	C	B-9	AH8325HGAC	—
					STR	BK	B-12	AH5464BK	AH5469BK
			QUICK		STR	Y	B-12	AH5464Y	AH5469Y
					STR	BK & W	B-12	5466N	5469N
			AUTO		STR	BK & W	B-12	5466N	5469N

 Hospital Grade

AMP	V/AC	NEMA	Color	Page	Flanged Inlet	Flanged Outlet
15	125	15-May	BK & W	B-10	AH5278C	AH5279C
			STEEL	B-10	AH5278	AH5246
20	125	20-May	BK & W	B-11	AH5778C	AH5779C
15	250	15-Jun	BK & W	B-11	AH5678C	AH5679C
20	250	20-Jun	BK & W	B-12	5878C	5879C

Compliances, specifications and availability are subject to change without notice.

www.eaton.com
www.eaton.com/arrowhart

Industrial grade straight blade devices

Product description


2-pole, 3-wire grounding
15A, 125V/AC
NEMA 5-15



5-15P



5-15R



AH5266



AH5969BK



AH5278C



AH5278

Industrial grade plugs & connectors



Rating A	V/AC	NEMA	Description	Cord diameter	Color	Plug catalog no.	Connector catalog no.		
15	125	5-15	Ultra grip straight body	0.33-0.66" (8.3-16.7mm)	BK & W	□ AH5266	□ AH5269	•	•
			Ultra grip straight body	0.33-0.66" (8.3-16.7mm)	BK	□ AH5266BK	□ AH5269BK	•	•
			Safety grip angled body	0.33-0.66" (8.3-16.7mm)	BK & W	□ AH5266A	—	•	•
			Quick grip straight body	0.22-0.66" (5.6-16.7mm)	BK	□ AH5965BK	□ AH5969BK	•	
			Quick grip straight body	0.22-0.66" (5.6-16.7mm)	Y	□ AH5965Y	□ AH5969Y	•	
			Auto grip straight body	0.33-0.66" (8.3-16.7mm)	BK & W	□ 5266N	□ 5269N	•	•

Industrial grade flanged inlets & outlets



Rating A	V/AC	NEMA	Description	Color	Inlet catalog no.	Outlet catalog no.	
15	125	5-15	Nylon construction, back wire	BK & W	□ AH5278C [†]	□ AH5279C [*]	•
			Metal shell, back wire	Steel	□ AH5278 ^Δ	□ AH5246	•

* UL and CSA Listed, [†] Fed Spec certified, ^ΔOnly NOM spec

Industrial grade dimensional
Information: B-16, B-17

Specification information:

Safety grip industrial plugs & connectors: B-24
Quick grip plugs & connectors: B-24
Auto grip industrial plugs & connectors: B-24
Industrial flanged inlets & Flanged outlets: B-25

Color information:

BK (Black), W (White), Y (Yellow)



Compliances, specifications and availability are subject to change without notice.



Indicates NAFTA compliant - Page Q-32



RoHS compliant - Page Q-32