



H7RICT

6" Aperture, Remodel, IC
120V Line Voltage

The H7 family of recessed housings are the standard in the industry for both commercial and residential applications. The wide variety of trims available allows a number of different lighting effects to be created with one basic housing. The H7RICT is designed for installations where the housing will be in direct contact with insulation. H7RICT may be converted into AIR-TITE installation when used with AIR-TITE trims. Look for the AIR-TITE trim logo in this section.



FEATURES

HOUSING

- Aluminum construction for greater heat dissipation.
- For installation from below the finished ceiling. Integral flange secures fixture against ceiling.

SOCKET PLATE

- Rigid socket plate adjusts and locks without tools for various lamp sizes.
- Socket plate and bracket may be removed when using socket supporting trims.

JUNCTION BOX

- Seven 1/2" trade size conduit knockouts with true pry-out slots are positioned to accommodate straight conduit runs.
- Four NM cable pryouts included.

"QUICK CONNECT" CONNECTORS

Three quick connect wiring connectors included.

REMODEL SPRINGS

Four remodel springs secure housing and accommodate 1/2" and 5/8" ceiling material.

SOCKET

Porcelain socket with nickel plated brass screw shell, snaps into socket plate (or into socket supporting trim for consistent lamp positioning.)

THERMAL PROTECTOR

Self resetting thermal protector deactivates fixture if overheating occurs due to improper lamping.

LABELS

- UL/cUL Listed 1598 Luminaire
- UL/cUL Damp Location Listed
- UL/cUL Listed for Wet Location, covered ceiling
- UL/cUL Listed for Feed Through
- UL/CUL Listed for direct contact with insulation and combustible material

