



H7ICTNB

6" Aperture, New Construction, IC 120V Line Voltage, No Socket Bracket

The H7 recessed housings are the standard in the industry for both commercial and residential applications. The wide variety of trims available allows a number of different lighting effects to be created with one basic housing. The H7ICTNB is designed for installations where the housing will be in direct contact with insulation. The H7ICTNB is designed to save installation time. It is designed without a socket plate for use with socket supporting trims only. With these trims there is no need to spend time removing the socket from the socket plate and the socket plate from the housing. H7ICTNB may be converted into AIR-TITE installation when used with AIR-TITE trims. Look for the AIR-TITE trim logo in this section.



FEATURES

HOUSING

- Aluminum construction for greater heat dissipation.
- Housing can be removed from the plaster frame for junction box access.

PLASTER FRAME

- Housing adjusts in plaster frame to accommodate up to 1-3/8" ceiling thickness.
- Galvanized steel construction.
- Plaster frame features include:
 - Regressed locking screw for securing hanger bars.
 - Cutouts for easily crimping hanger bars in position.
 - HALO name embossed on plaster frame.
 - The housing may be removed from plaster frame to provide access to the junction box.

SLIDE-N-SIDE™ JUNCTION BOX

- Positioned to accommodate straight conduit runs
- Seven 1/2" trade size conduit knockouts with true pry-out slots
- Slide-N-Side™ wire traps allow non metallic sheathed cable to be installed without tools and without removing knockouts.
- Accepts a wide range of non-metallic (type NM) sheathed cables - the standard cable types used in lighting in both U.S. and Canada.
 - Allows wiring connections to be made outside the junction box
 - Simply insert the cable directly into the trap after connections are made.
 - Accommodates the following standard non-metallic sheathed cable sizes:
 - (US) #14/2, #14/3, #12/2, #12/3
 - (Canada) #14/2, #14/3, #12/2

"QUICK CONNECT" CONNECTORS

Three quick connect wiring connectors included.

Got NAIL!™ Pass-N-Thru™ BAR HANGERS

- Pre-installed nail easily installs in regular lumber, engineered lumber and laminated beams.
- Safety and guidance system prevents snagging, ensures smooth straight nail penetration and allows bar hangers to be easily removed if necessary.
- Automatic levelling flange aligns the housing and lets you hold the housing in place with one hand while driving nails.
- Housing can be positioned at any point within 24" joist span.
- Pass-N-Thru™ feature allows bar hangers to be shortened without removing from plaster frame.
- Score lines allow "tool-less" shortening for 12" joists.
- Bar hangers may be repositioned 90°.
- Integral T-bar clip snaps onto T-bars - no additional clips required.

SOCKET

Porcelain socket with nickel plated brass screw shell, snaps into trim for consistent lamp positioning.

THERMAL PROTECTOR

Self resetting thermal protector deactivates fixture if overheating occurs due to improper lamping.

LABELS

- UL/cUL Listed 1598 Luminaire
- UL/cUL Listed for Damp Location
- UL/cUL Listed for Wet Location, covered ceiling
- UL/cUL Listed for Feed Through
- UL/CUL Listed for direct contact with insulation and combustible material

