

StreetSense LED Streetlight

Ordering Information and Mounting Accessories

Part Number ¹	Number of Light Engines	EPA (SQ. ft)	BUG Rating	Voltage	Lens	CCT	Fixture Lumens	Watt	LPW	Light Distribution Pattern
Standard Models - 100 - 277V AC										
SL3C5CLGG	1	0.60	B1U1G1	100 - 277V AC	Tempered glass	5000K (cool white)	5,500	65	85	Type III
SL3C5DLGG	1	0.60	B2U1G2	100 - 277V AC	Tempered glass	5000K (cool white)	6,800	83	82	Type III
SL3C5HLGG	2	0.87	B2U1G2	100 - 277V AC	Tempered glass	5000K (cool white)	10,900	131	83	Type III
SL3C5ILGG	2	0.87	B3U1G3	100 - 277V AC	Tempered glass	5000K (cool white)	13,300	165	81	Type III
SL3C5RLGG	3	1.13	B3U1G3	100 - 277V AC	Tempered glass	5000K (cool white)	16,000	190	84	Type III
SL3C5SLGG	3	1.13	B3U1G3	100 - 277V AC	Tempered glass	5000K (cool white)	20,250	252	80	Type III
Standard models - 347 - 480V AC										
SL3C7CLGG	1	0.60	B1U1G1	347 - 480V AC	Tempered glass	5000K (cool white)	5,500	65	85	Type III
SL3C7DLGG	1	0.60	B2U1G2	347 - 480V AC	Tempered glass	5000K (cool white)	6,800	83	82	Type III
SL3C7HLGG	2	0.87	B2U1G2	347 - 480V AC	Tempered glass	5000K (cool white)	10,900	131	83	Type III
SL3C7ILGG	2	0.87	B3U1G3	347 - 480V AC	Tempered glass	5000K (cool white)	13,300	165	81	Type III
SL3C7RLGG	3	1.13	B3U1G3	347 - 480V AC	Tempered glass	5000K (cool white)	16,000	190	84	Type III
SL3C7SLGG	3	1.13	B3U1G3	347 - 480V AC	Tempered glass	5000K (cool white)	20,250	252	80	Type III

All values typical unless otherwise stated, Lumen values are typical (tolerance +/- 10%).

Part numbers listed in the above table are cool white. For neutral white model, replace the 4th character with **N** Ex: SL3C5CLGG becomes SL3N5CLGG



SLSHIELDKIT

- House Side Shield



SL-PC01R

- 105 - 305V AC Photocontroller

SL-PC02R

- 312 - 382V AC Photocontroller

SL-PC03R

- 432 - 528V AC Photocontroller