

Key Operated Selector Switches

Key removal from maintained positions only—will accept a maximum of two contact blocks (four circuits) with supplied three-way mounting adapter. Optional five-way adapter will accept a maximum of five contact blocks (10 circuits).

Plastic Black Bezel**Plastic Chrome Bezel****Metal Chrome Bezel****Key Operated Selector Switches—UL (NEMA) Type 3, 3R, 4, 4X, 12, 13****Operating Mode****M = Maintained****S = Momentary****Cam Code****E22 Series—Plastic Operators****45° Black Bezel Catalog Number ①****45° Chrome Bezel Catalog Number ①****EM22 Series—Metal Operators****60° Chrome Bezel Catalog Number ①****Two-Position**

M	—	M	2	E22KB52	E22K52	—
M	—	M	2	E22KB53	E22K53	EM22K53
M	—	S	2	E22KB62	E22K62	EM22K62
—	M	M	2	E22KBF4	E22KF4	EM22KF4

Three-Position


M	M	M	1	E22KBG7	E22KG7	—
---	---	---	---	----------------	---------------	---

Spare Key

Description	Reference Number Stamped on Key	Catalog Number
Standard lock	92239	E22KS2

Specialty Operators**Mechanical Push Rod****Flush Pushbutton Operators with Mechanical Push Rod—UL (NEMA) Type 3, 3R, 4, 4X, 12, 13**

Description	Color	Plastic—Black Bezel Catalog Number	Plastic—Chrome Bezel Catalog Number
25 mm diameter flush pushbutton Operators supplied with mechanical push rod—suitable for external mechanical reset of overload relays. Push rod must be cut to desired length	Gray	E22PB7L	E22P7L

Double-Headed Pushbuttons**Double-Headed Pushbuttons****Illuminated and Non-Illuminated Double-Headed Pushbuttons—UL (NEMA) Type 1; IP40**

Description	Operator Colors	Marking	Plastic—Black Bezel Catalog Number
Non-illuminated double-headed pushbutton	Green—Red	I	E22DB1A21

Contact Blocks**Contact Blocks****Contact Blocks**

Description	Catalog Number
1NC	E22B1 ②
1NO	E22B2
1NO-1NC	E22B11 ②
2NO	E22B20
One self-monitoring 1NC	E22CB1M ②③

Notes

① Final digit of catalog number represents key removal position per the chart below.

Key Removal Position	Code Suffix	Key Removal Position	Code Suffix
Left only	2	Center only	4
Right and left	3	Right, left and center	7

② Marked with direct opening action (DOA) symbol per IEC 60947-5-1 (Annex K) and NEMA ICS 5 (Part 6).

③ For use with trigger action emergency stop (E22LTA2) operators.