

Eaton 170F8230

Catalog Number: 170F8230

Fuse-link, high speed, 160 A, DC 1200 V, size 2, 65 x 90 x 165 mm, aR, IEC, with indicator

General specifications



Product Name	Catalog Number
Eaton Bussmann series high speed traction fuse	170F8230
	UPC
	051712491327
EAN	Product Length/Depth
5996516007617	165 mm
Product Height	Product Width
90 mm	66 mm
Product Weight	Compliances
1051 g	CE
	RoHS Compliant
	EAC
Certifications	
IEC 60269-4	

defaultTaxonomyAttributeLabel

Type

Fuse

Application

traction

Amperage Rating

160 A

Breaking capacity

100 kA

Voltage type

DC

Utilization category

aR (accompanied semiconductor protection)

Insulated metal gripping lugs (IMGL)

No

Fuse indicator

Other

Fuse size

2

Class

Class aR

Clearing (I2T)

20000 at 1000 Vdc

Watt losses

75 W

Fuse shape

Square body, offset bolted tags

Mounting dimension

M8

Center-to-center distance of connections

142 mm

Current type

DC

Rated voltage DC

1200 V

Color

Resources

Catalogs

Traction fuse-links

None

Interrupt rating

100 kAIC

Construction size

2

Packaging type

Standard

Voltage rating

1200 V

Fitted with:

Double slot tags

Fuse system (according to IEC 60269)

Other



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia