

Eaton 250NHG2B

Catalog Number: 250NHG2B

Fuse-link, low voltage, 250 A, AC 500 V, NH2, gL/gG, IEC, dual indicator

General specifications



Product Name	Catalog Number
Eaton Bussmann series low voltage NH Fuse	250NHG2B
	Model Code
	NH FUSE 250A 500V gG SIZE 2 DUAL IND
UPC	EAN
051712683722	5027590469739
Product Length/Depth	Product Height
150 mm	71 mm
Product Width	Product Weight
53 mm	651 g
Compliances	Certifications
CE Marked	IEC 60269-1
RoHS Compliant	IEC 60269-2
	DIN 43620

Type

Fuse

Application

industrial

Utilities, Solar, Wind

Amperage Rating

250 A

Fitted with:

Insulated metal gripping lugs

Fuse size

NH02

Current type

AC

Breaking capacity

120 kA

Rated switching capacity

120 kA

Rated voltage AC

500 V

Class

Class gG/gL

Fuse type

Square body with knife blade contact

Utilization category

gL/gG (cable protection/equipment protection)

Interrupt rating

120 kAIC

Fuse indicator

Combination fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Watt losses

23 W

Connection

Blade end

Catalogs[eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf](#)[NH Fuse links, bases and gear](#)[CA134002EN](#)**Compliance information**[UKCA Size 2 NH 500V](#)**Multimedia**[Eaton Bussmann – NH fuse link portfolio](#)**Presentations**[NH Overview Video](#)**Technical data sheets**[10164 NH 500 Volts gG](#)**Technical service bulletins**[Datasheet - 250NHG2B](#)

Construction

NH2

Construction size

NH2

Fuse shape

Square body

Knife blade contacts

Voltage type

AC

Suitable for

Microswitch BVL50

Material

Ceramic body

Quantity

3

Voltage rating

500 V

Rated switching capacity AC

120 kA



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



Eaton.com/socialmedia