

Eaton Z48D28T15CUS64X

Catalog Number: Z48D28T15CUS64X

Eaton Hazardous location encapsulated transformer, Class 1 Division 2 Groups A, B, C, D, Three-phase, PV: 480V, Taps: 2 at +5% FCAN, 2 at -5% FCBN, SV: 208Y/120V, 115°C, 15 kVA, Cu windings, NEMA 4X, Frame: 95H4X , Indoor-Outdoor

General specifications



Photo is representative

Product Name	Catalog Number
Eaton Hazardous location encapsulated transformer	Z48D28T15CUS64X
	UPC
	786680240171
Product Length/Depth	Product Height
11.91 in	15.55 in
Product Width	Product Weight
23.48 in	293 lb
Compliances	Certifications
Class I, Div. 2, Groups A, B, C, D	UL Listed

defaultTaxonomyAttributeLabel

Special features

316 SS NEMA 4X

Type

Class 1 Division 2 Groups C and D, Hazardous Location
Transformer

Coil material

Copper

Frequency rating

50/60 Hz

Kva Rating

15 kVA

kVA

15 kVA

Mounting

Wall Mount

Phase

Three-phase

Primary voltage

480 V

Secondary Voltage

208Y/120 V

Sound Level

NEMA ST-20

Temperature rise

115 °C rise

Design

EPTZ

Area classification

Hazardous/Classified Locations

Enclosure

NEMA 4X

Frame

95H4X

Insulation

180 °C

Resources

Catalogs

[Transformer distribution catalog](#)

Specifications and datasheets

[Eaton Specification Sheet - Z48D28T15CUS64X](#)

Tap size

2 at +5% FCAN, 2 at -5% FCBN

Volt ampere rating

15 kVA

Weathershield

Indoor-Outdoor

Wiring connection

65F



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia