

Specifications

Eaton DD327FDKW-00LO

Eaton Double door single-throw fused safety switch, 800 A, NEMA 12/3R, Painted galvanized steel, Class L, Fusible without neutral, Three-pole, Three-wire, 240 V, Max Hp: 500, 500 hp (3PH @480, 240 V), (4) 1/0 - (4) 750 kcmil



General specifications

PRODUCT NAME	Eaton double door single-throw fused safety switch
CATALOG NUMBER	DD327FDKW-00LO
UPC	786689211936
PRODUCT LENGTH/DEPTH	82.25 in
PRODUCT HEIGHT	17.125 in
PRODUCT WIDTH	25.25 in
PRODUCT WEIGHT	300 lb
CERTIFICATIONS	UL Listed
CATALOG NOTES	Double Door Isolation Switch

Physical Attributes

ENCLOSURE	NEMA 12, NEMA 3R
ENCLOSURE MATERIAL	Painted galvanized steel
FUSE CONFIGURATION	Fusible without neutral
NUMBER OF POLES	Three-pole
NUMBER OF WIRES	3
TYPE	Heavy duty double door safety switch

Miscellaneous

PRODUCT CATEGORY	Dust tight
SPECIAL FEATURES	w/ window, Lock-On Provision

Performance Ratings

AMPERAGE RATING	800A
FUSE CLASS PROVISION	Class L
HP RATING - MAX	500, 500 hp (3PH @480, 600 V)
NEMA RATING	NEMA 12
VOLTAGE RATING	240V

Resources

MULTIMEDIA

[Flex Center Customized Double Door Switch with Voltage Indicator and Safe-Test Point](#)

[Double Up on Safety](#)

[Double Door Line Isolation
Safety Switch](#)

[Switching Devices Flex Center](#)

[ARMS Enclosed Circuit
Breaker](#)

**SPECIFICATIONS AND
DATASHEETS**

[Eaton Specification Sheet -
DD327FDKW-00LO](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights
Reserved.

Eaton is a registered trademark. Follow us on social media to get the latest
All other trademarks are property of product and support information.
their respective owners.

