

Specifications



Photo is representative

Eaton DD362FDKW-00LO

Eaton Double door single-throw fused safety switch, 60 A, NEMA 12/3R, Painted galvanized steel, Class H, Fusible without neutral, 3P, Three-wire, 600 V, Max Hp: 20, 25/ 30, 50 hp (1/3PH @480, 600 V), #14-#2

General specifications

PRODUCT NAME	Eaton double door single-throw fused safety switch
CATALOG NUMBER	DD362FDKW-00LO
UPC	786689211950
PRODUCT LENGTH/DEPTH	37.49 in
PRODUCT HEIGHT	8.22 in
PRODUCT WIDTH	9.3 in
PRODUCT WEIGHT	37 lb
CERTIFICATIONS	UL Listed
CATALOG NOTES	Double Door Isolation Switch



Physical Attributes

ENCLOSURE	NEMA 12, NEMA 3R
-----------	------------------

Performance Ratings

AMPERAGE RATING	60A
-----------------	-----

ENCLOSURE MATERIAL	Painted galvanized steel
FUSE CONFIGURATION	Fusible without neutral
NUMBER OF POLES	Three-pole
NUMBER OF WIRES	3
TYPE	Heavy duty double door safety switch
WIRE SIZE	#14-2 AWG

FUSE CLASS PROVISION	Class H
HP RATING - MAX	20, 25/ 30, 50 hp (1/3PH @480, 600 V)
NEMA RATING	NEMA 12
VOLTAGE RATING	600 V

Miscellaneous	
PRODUCT CATEGORY	Dust tight
SPECIAL FEATURES	w/ window, Lock-On Provision

Resources	
	Flex Center Customized Double Door Switch with Voltage Indicator and Safe-Test Point
	Double Up on Safety
MULTIMEDIA	ARMS Enclosed Circuit Breaker
	Switching Devices Flex Center
	Double Door Line Isolation Safety Switch
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - DD362FDKW-00LO

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.

