

Specifications

Eaton DD364FDKW-00LO

Eaton Double door single-throw fused safety switch, 200 A, NEMA 12/3R, Painted galvanized steel, Class H, Fusible without neutral, 3-pole, Three-wire, 600 V, Max Hp: 50, 50/ 125, 150 hp (1/3PH @ 480, 600 V), #6-300 kcmil



General specifications

PRODUCT NAME	Eaton double door single-throw fused safety switch
CATALOG NUMBER	DD364FDKW-00LO
UPC	786689211899
PRODUCT LENGTH/DEPTH	49.9 in
PRODUCT HEIGHT	11.62 in
PRODUCT WIDTH	17.18 in
PRODUCT WEIGHT	85 lb
CERTIFICATIONS	UL Listed
CATALOG NOTES	Double Door Isolation Switch

Physical Attributes

ENCLOSURE	NEMA 12, NEMA 3R
ENCLOSURE MATERIAL	Painted galvanized steel
FUSE CONFIGURATION	Fusible without neutral
NUMBER OF POLES	Three-pole
NUMBER OF WIRES	3
TYPE	Heavy duty double door safety switch

Miscellaneous

PRODUCT CATEGORY	Dust tight
SPECIAL FEATURES	w/ window, Lock-On Provision

Performance Ratings

AMPERAGE RATING	200A
FUSE CLASS PROVISION	Class H
HP RATING - MAX	50, 50/ 125, 150 hp (1/3PH @480, 600 V)
NEMA RATING	NEMA 12
VOLTAGE RATING	600 V

Resources

MULTIMEDIA	Switching Devices Flex Center ARMS Enclosed Circuit Breaker
------------	--

[Flex Center Customized
Double Door Switch with
Voltage Indicator and Safe-
Test Point](#)

[Double Door Line Isolation
Safety Switch](#)

[Double Up on Safety](#)

SPECIFICATIONS AND DATASHEETS
--

Eaton Specification Sheet - DD364FDKW-00LO
--

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights
Reserved.

Eaton is a registered trademark. Follow us on social media to get the latest
product and support information.
All other trademarks are property of
their respective owners.

