

Eaton DD368FDKW-00LO

Catalog Number: DD368FDKW-00LO

Eaton Double door single-throw fused safety switch, 1200 A, NEMA 12/3R, Painted galvanized steel, Class L, Fusible without neutral, Three-pole, Three-wire, 600 V, Max Hp: 500, 500 hp (3PH @480, 600 V), (4) 1/0 - (4) 750 kcmil

General specifications

Product Name	Catalog Number
Eaton double door single-throw fused safety switch	DD368FDKW-00LO
	UPC
	786689211912
Product Length/Depth	Product Height
27.18 in	43.11 in
Product Width	Product Weight
91.02 in	575 lb
Certifications	Catalog Notes
UL Listed	Double Door Isolation Switch



Physical Attributes

Enclosure

NEMA 12, NEMA 3R

Enclosure material

Painted galvanized steel

Fuse configuration

Fusible without neutral

Number Of Poles

Three-pole

Number of wires

3

Type

Heavy duty double door safety switch

Performance Ratings

Amperage Rating

1200A

Fuse class provision

Class L

HP rating - max

500, 500 hp (3PH @480, 600 V)

NEMA rating

NEMA 12

Voltage rating

600 V

Miscellaneous

Product Category

Dust tight

Special features

w/ window, Lock-On Provision

Resources

Multimedia

[Double Door Line Isolation Safety Switch](#)

[ARMS Enclosed Circuit Breaker](#)

[Flex Center Customized Double Door Switch with Voltage Indicator and Safe-Test Point](#)

[Double Up on Safety](#)

[Switching Devices Flex Center](#)

Specifications and datasheets

[Eaton Specification Sheet - DD368FDKW-00LO](#)

Warranty guides

[Selling Policy 25-000 - Distribution and Control Products and Services](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)