



Automotive & Miniature Lamps

EIKO's line of original equipment headlamps and miniature indicator and accent lamps were designed to meet or exceed the performance of your vehicle's original lamp. Manufactured to exacting standards, they feature top quality components and are guaranteed to perform like the original. Our metal-based lamps also feature an industry-first, nickel-plated brass base which prevents corrosion and ensures performance. Additionally, each and every lamp is quality tested before it leaves the factory.

CLEAR VISION®
Supreme

Clear Vision® Supreme High Performance Forward Lighting

Item	Order Code	Watts	Volts	Base	Filament	Lumens	MOL in/mm	MOD in/mm	Life
880CVSU-BP	07021	27	12.8	PG13	C-6		2.68/68.1	0.42/10.7	500
881CVSU-BP	07033	27	12.8	PGJ13	C-6		2.68/68.1	0.42/10.7	500
889CVSU-BP	07018	27	12.8	PGJ13	C-6		2.68/68.1	0.42/10.7	500
893CVSU-BP	07035	37.5	12.8	PG13	C-6		2.68/68.1	0.42/10.7	500
894CVSU-BP	07043	37.5	12.8	PGJ13	C-6		2.68/68.1	0.42/10.7	500
896CVSU-BP	07001	37.5	12.8	PGJ13	C-6		2.68/68.1	0.42/10.7	500
899CVSU-BP	01206	37.5	12.8	PG13	C-6		2.68/68.1	0.42/10.7	1,900
H1042CVSU-BP	07680	42	13.2	PY20d	CC-8	840	3.17/80.5	0.47/11.8	775
H1042CVSU2	07062	42	13.2	PY20d	CC-8	840	3.17/80.5	0.47/11.8	775
885CVSU-BP	07013	50	12.8	PG13	C-6	1320	2.68/68.1	0.42/10.7	500
9006CVSU-BP	07677	55	12.8	P22d	C-8	1005	3.09/78.0	0.42/10.7	1,000
9006CVSU2	02434	55	12.8	P22d	C-8	1005	3.09/78.0	0.42/10.7	1,000
9006XSCVSU-BP	07674	55	12.8	P22d	C-8	1005	2.61/66.29	0.42/10.7	1,000
9006XSCVSU2	07673	55	12.8	P22d	C-8	1005	2.61/66.29	0.42/10.7	1,000
H1155CVSU-BP	07681	55	13.2	PGJ19-2	CC-8	1345	2.64/67	0.43/10.8	550
H1155CVSU2	07008	55	13.2	PGJ19-2	CC-8	1345	2.64/67	0.43/10.8	550
H11BCVSU-BP	07682	55	13.2	PGJY19-2	CC-8	1345	2.63/66.8	0.43/10.8	1,000
H11BCVSU2	07010	55	13.2	PGJY19-2	CC-8	1345	2.63/66.8	0.43/10.8	1,000
H155CVSU-BP	07683	55	12	P14.5s	C-8	1545	2.65/67.3	0.33/8.4	225

>>Continued on page 43



880 / 893 / 899 CVSu



881 / 896 CVSu



889 / 894 CVSu



885 CVSu



H155 CVSu



H1155 CVSu



Miniature Lamps (Alphanumeric)

Item	Order Code	Amps	Volts	Base	Filament	MOL in/mm	MOD in/mm	Life
89-BP	40996	0.58	13	BA15s	C-6	1.44/36.6	0.75/19.1	750
89K	01785	0.58	13	E12	C-2R	1.38/35.1	0.75/19.1	750
90	41005	0.58	13	BA15d	C-6	1.44/36.6	0.75/19.1	750
90-BP	41006	0.58	13	BA15d	C-6	1.44/36.6	0.75/19.1	750
90MB	40886	0.03	90	BA9s	CC-7A	1.19/30.2	0.33/8.4	5,000
93	41033	1.04	12.8	BA15s	C-6	2.00/50.8	1.04/26.4	700
93-BP	41034	1.04	12.8	BA15s	C-6	2.00/50.8	1.04/26.4	700
94	41037	1.04	12.8	BA15d	C-6	2.00/50.8	1.04/26.4	700
96	41041	0.69	13.5	BA15d	C-2V	1.44/36.6	0.75/19.1	5,000
97	41043	0.69	13.5	BA15s	C-6	1.44/36.6	0.75/19.1	5,000
97A	41046	0.69	13.5	BA15s	C-6	1.44/36.6	0.75/19.1	5,000
97-BP	41044	0.69	13.5	BA15s	C-6	1.44/36.6	0.75/19.1	5,000
98	41048	0.62	13	BA15s	C-6	1.44/36.6	0.75/19.1	800
105	40163	1.0	12.8	BA15s	C-6	1.75/44.5	0.79/20.1	500
105-BP	42026	1.0	12.8	BA15s	C-6	1.75/44.5	0.79/20.1	500
112	40168	0.25	1.2	E10	S-2	0.93/23.6	0.38/9.6	5
120MB	40226	0.025	120	BA9s	CC-7A	1.19/30.2	0.33/8.4	10,000
120MB/6	44022	0.052	120	BA9s	CC-7A	1.19/30.2	0.33/8.4	3,000
120MB-Neon	40225	0.004	120	BA9s	Neon	1.19/30.2	0.38/9.6	10,000
120PSB5	40230	0.025	120	TS5	CC-7A	1.11/28.2	0.27/6.9	10,000
120PSB5-Neon	40229	0.0035	120	TS5	Neon	1.12/28.5	0.27/6.9	10,000
120RB	40231	0.025	120	BA9s	CC-7A	1.16/29.5	0.91/23.1	7,500
120RC	40253	0.025	120	E12	CC-7A	1.22/31.0	0.91/23.1	7,500
120RC-Neon	40297	0.0035	120	E12	Neon	1.22/31.0	0.91/23.1	10,000
123	40237	0.3	1.25	E10	S-2	0.94/23.9	0.43/11.0	10
124	40238	0.27	14	W2.1x9.5d	C-2F	1.06/26.9	0.40/10.2	5,000
130	49671	0.15	6.3	BA9s	C-2R	0.94/23.9	0.43/11.0	5,000
130MB	40249	0.025	130	BA9s	CC-7A	1.19/30.2	0.33/8.4	10,000
131	40252	0.1	1.3	E10	S-2	0.94/23.9	0.43/11.0	50
147	40278	0.43	7	W2.1x9.5d	C-2R	1.06/26.9	0.40/10.2	1,500
155MB	40296	0.025	155	BA9s	CC-7A	1.19/30.2	0.33/8.4	10,000
155PSB5	40298	0.025	155	TS5	CC-7A	1.11/28.2	0.27/6.9	10,000
158	40300	0.24	14	W2.1x9.5d	C-2V	1.06/26.9	0.40/10.2	500
158-BP	40301	0.24	14	W2.1x9.5d	C-2V	1.06/26.9	0.40/10.2	500
159	40303	0.15	6.3	W2.1x9.5d	C-2R	1.06/26.9	0.40/10.2	5,000
161	40304	0.19	14	W2.1x9.5d	C-2F	1.06/26.9	0.40/10.2	4,000
161-BP	42030	0.19	14	W2.1x9.5d	C-2F	1.06/26.9	0.40/10.2	4,000
168	40317	0.35	14	W2.1x9.5d	C-2F	1.06/26.9	0.40/10.2	1,500
168-BP	40318	0.35	14	W2.1x9.5d	C-2F	1.06/26.9	0.40/10.2	1,500
168LL	42502	0.35	14	W2.1x9.5d	C-2F	1.06/26.9	0.40/10.2	3,000
168LL-BP	40337	0.35	14	W2.1x9.5d	C-2F	1.06/26.9	0.40/10.2	3,000
168NA	00227	0.35	14	W2.1x9.5d	C-2F	1.06/26.9	0.40/10.2	1,500
168NA-BP	00228	0.35	14	W2.1x9.5d	C-2F	1.06/26.9	0.40/10.2	1,500
192	40424	0.33	13	W2.1x9.5d	C-2V	1.06/26.9	0.40/10.2	1,000
192-BP	42344	0.33	13	W2.1x9.5d	C-2V	1.06/26.9	0.40/10.2	1,000
193	40426	0.33	14	W2.1x9.5d	C-2F	1.06/26.9	0.40/10.2	15,000
194	40427	0.27	14	W2.1x9.5d	C-2F	1.06/26.9	0.40/10.2	2,500
194A	40430	0.27	14	W2.1x9.5d	C-2F	1.06/26.9	0.40/10.2	2,500
194A-BP	40431	0.27	14	W2.1x9.5d	C-2F	1.06/26.9	0.40/10.2	2,500
194B	42438	0.27	14	W2.1x9.5d	C-2F	1.06/26.9	0.40/10.2	2,500
194B-BP	42440	0.27	14	W2.1x9.5d	C-2F	1.06/26.9	0.40/10.2	2,500
194-BP	40428	0.27	14	W2.1x9.5d	C-2F	1.06/26.9	0.40/10.2	2,500
194G	00794	0.27	14	W2.1x9.5d	C-2F	1.06/26.9	0.40/10.2	2,500
194G-BP	49830	0.27	14	W2.1x9.5d	C-2F	1.06/26.9	0.40/10.2	2,500
194LL	42504	0.27	14	W2.1x9.5d	C-2F	1.06/26.9	0.40/10.2	5,000
194LL-BP	40335	0.27	14	W2.1x9.5d	C-2F	1.06/26.9	0.40/10.2	5,000