



Automotive & Miniature Lamps

EIKO's line of original equipment headlamps and miniature indicator and accent lamps were designed to meet or exceed the performance of your vehicle's original lamp. Manufactured to exacting standards, they feature top quality components and are guaranteed to perform like the original. Our metal-based lamps also feature an industry-first, nickel-plated brass base which prevents corrosion and ensures performance. Additionally, each and every lamp is quality tested before it leaves the factory.

CLEAR VISION®
Supreme

Clear Vision® Supreme High Performance Forward Lighting

Item	Order Code	Watts	Volts	Base	Filament	Lumens	MOL in/mm	MOD in/mm	Life
880CVSU-BP	07021	27	12.8	PG13	C-6		2.68/68.1	0.42/10.7	500
881CVSU-BP	07033	27	12.8	PGJ13	C-6		2.68/68.1	0.42/10.7	500
889CVSU-BP	07018	27	12.8	PGJ13	C-6		2.68/68.1	0.42/10.7	500
893CVSU-BP	07035	37.5	12.8	PG13	C-6		2.68/68.1	0.42/10.7	500
894CVSU-BP	07043	37.5	12.8	PGJ13	C-6		2.68/68.1	0.42/10.7	500
896CVSU-BP	07001	37.5	12.8	PGJ13	C-6		2.68/68.1	0.42/10.7	500
899CVSU-BP	01206	37.5	12.8	PG13	C-6		2.68/68.1	0.42/10.7	1,900
H1042CVSU-BP	07680	42	13.2	PY20d	CC-8	840	3.17/80.5	0.47/11.8	775
H1042CVSU2	07062	42	13.2	PY20d	CC-8	840	3.17/80.5	0.47/11.8	775
885CVSU-BP	07013	50	12.8	PG13	C-6	1320	2.68/68.1	0.42/10.7	500
9006CVSU-BP	07677	55	12.8	P22d	C-8	1005	3.09/78.0	0.42/10.7	1,000
9006CVSU2	02434	55	12.8	P22d	C-8	1005	3.09/78.0	0.42/10.7	1,000
9006XSCVSU-BP	07674	55	12.8	P22d	C-8	1005	2.61/66.29	0.42/10.7	1,000
9006XSCVSU2	07673	55	12.8	P22d	C-8	1005	2.61/66.29	0.42/10.7	1,000
H1155CVSU-BP	07681	55	13.2	PGJ19-2	CC-8	1345	2.64/67	0.43/10.8	550
H1155CVSU2	07008	55	13.2	PGJ19-2	CC-8	1345	2.64/67	0.43/10.8	550
H11BCVSU-BP	07682	55	13.2	PGJY19-2	CC-8	1345	2.63/66.8	0.43/10.8	1,000
H11BCVSU2	07010	55	13.2	PGJY19-2	CC-8	1345	2.63/66.8	0.43/10.8	1,000
H155CVSU-BP	07683	55	12	P14.5s	C-8	1545	2.65/67.3	0.33/8.4	225

>>Continued on page 43



880 / 893 / 899 CVSu



881 / 896 CVSu



889 / 894 CVSu



885 CVSu



H155 CVSu



H1155 CVSu



Miniature Lamps (Alphanumeric)

Item	Order Code	Amps	Volts	Base	Filament	MOL in/mm	MOD in/mm	Life
194NA	40432	0.27	14	W2.1x9.5d	C-2F	1.06/26.9	0.40/10.2	2,500
194NA-BP	40433	0.27	14	W2.1x9.5d	C-2F	1.06/26.9	0.40/10.2	2,500
194R	42442	0.27	14	W2.1x9.5d	C-2F	1.06/26.9	0.40/10.2	2,500
194R-BP	42444	0.27	14	W2.1x9.5d	C-2F	1.06/26.9	0.40/10.2	2,500
198	40443	2.25/0.59	12.8/14	BAY15d	C-6/C-6	2.00/50.8	1.04/26.4	1200 / 5000
198-BP	42032	2.25/0.59	12.8/14	BAY15d	C-6/C-6	2.00/50.8	1.04/26.4	1200 / 5000
198LL	42508	2.25/0.59	12.8/14	BAY15d	C-6/C-6	2.00/50.8	1.04/26.4	2400 / 10000
199	40445	2.25	12.8	BA15s	C-6	2.00/50.8	1.04/26.4	1,200
200	00805	0.85	4.0	BA15d	C-6	1.44/36.6	0.75/19.1	50
210	40454	1.78	6.5	BA15d	C-6	1.75/44.5	0.79/20.1	100
211-2	40480	0.97	12.8	Double End Cap	C-8	1.72/43.7	0.38/9.6	1,000
211-2B	00837	0.37	12.8	Double End Cap	C-8	1.72/43.7	0.43/11.0	1,000
211-2B-BP	00838	0.37	12.8	Double End Cap	C-8	1.72/43.7	0.43/11.0	1,000
211-2-BP	40481	0.97	12.8	Double End Cap	C-8	1.72/43.7	0.38/9.6	1,000
211-2/F	42312	0.97	12.8	SV8.5mm	C-8	1.72/43.7	0.42/10.54	1,000
211-2/F-BP	42238	0.97	12.8	SV8.5mm	C-8	1.72/43.7	0.42/10.54	1,000
211-2R-BP	00841	0.37	12.8	Double End Cap	C-8	1.72/43.7	0.43/11.0	1,000
212-2	42256	0.74	13.5	Double End Cap	C-8	1.72/43.7	0.38/9.6	2,000
212-2-BP	42036	0.74	13.5	Double End Cap	C-8	1.72/43.7	0.38/9.6	2,000
214-2	42040	0.52	13.5	Double End Cap	C-8	1.72/43.7	0.38/9.6	1,000
219	49701	0.25	6.3	BA9s	C-2V	0.94/23.9	0.43/11.0	5,000
222	40492	0.25	2.25	E10	C-2R	0.93/23.6	0.38/9.6	5
222-BP	40493	0.25	2.25	E10	C-2R	0.93/23.6	0.38/9.6	5
233	49702	0.27	2.33	E10	C-2R	0.94/23.9	0.43/11.0	10
238	49704	0.5	6.3	BA9s	C-2R	1.19/30.2	0.43/11.0	2,000
239	00929	0.36	6.3	BA9s	C-2R	1.19/30.2	0.43/11.0	5000 +
243	40520	0.27	2.33	E10	C-6	0.93/23.6	0.38/9.6	10
245	49703	0.5	2.46	E10	C-2R	0.94/23.9	0.43/11.0	15
251	40524	0.3	2.47	SX6s	C-2R	0.63/16.0	0.23/5.9	30
257	49674	0.27	14	BA9s	C-2R	1.07/27.2	0.59/15.0	500
258	49706	0.27	14	E10	C-2R	1.07/27.2	0.59/15.0	500
259	40534	0.25	6.3	W2.1x9.5d	C-2R	1.06/26.9	0.40/10.2	5,000
265	49707	0.08	28	BA9s	C-2F	0.94/23.9	0.43/11.0	5,000
267	01034	0.15	6.3	BA9s	C-2R	1.19/30.2	0.43/11.0	5,000
293	40550	0.33	14	BA9s	C-2F	1.07/27.2	0.59/15.0	5,000
293-BP	42044	0.33	14	BA9s	C-2F	1.07/27.2	0.59/15.0	5,000
301	49448	0.17	28	BA15s	C-2F	1.38/35.1	0.62/15.8	500
303	40562	0.3	28	BA15s	CC-6	1.44/36.6	0.75/19.1	500
304	49103	0.3	28	BA15d	C-2F	1.44/36.6	0.75/19.1	500
306	40566	0.51	28	BA15d	C-6	2.00/50.8	1.04/26.4	300
307	40568	0.67	28	BA15s	C-6	2.00/50.8	1.04/26.4	300
308	40570	0.67	28	BA15d	C-6	2.00/50.8	1.04/26.4	300
311	40576	1.29	28	BA15s	CC-2V	2.38/60.5	1.35/34.3	300
312	01125	1.29	28	BA15d	C-2V	2.38/60.45	1.42/36	300
313	40578	0.17	28	BA9s	C-2F	1.19/30.2	0.43/11.0	500
313-BP	81130	0.17	28	BA9s	C-2F	1.19/30.2	0.43/11.0	500
313-R	01132	0.17	28	BA9s	C-2F	1.19/30.2	0.43/11.0	500
315	40580	0.9	28	BA15s	CC-6	2.00/50.8	1.04/26.4	300
327	40596	0.04	28	SX6s	C-2F	0.63/16.0	0.23/5.9	4,000
328	40598	0.2	6	SX6s	C-2R	0.63/16.0	0.23/5.9	1,000