



Automotive & Miniature Lamps

EIKO's line of original equipment headlamps and miniature indicator and accent lamps were designed to meet or exceed the performance of your vehicle's original lamp. Manufactured to exacting standards, they feature top quality components and are guaranteed to perform like the original. Our metal-based lamps also feature an industry-first, nickel-plated brass base which prevents corrosion and ensures performance. Additionally, each and every lamp is quality tested before it leaves the factory.

CLEAR VISION®
Supreme

Clear Vision® Supreme High Performance Forward Lighting

Item	Order Code	Watts	Volts	Base	Filament	Lumens	MOL in/mm	MOD in/mm	Life
880CVSU-BP	07021	27	12.8	PG13	C-6		2.68/68.1	0.42/10.7	500
881CVSU-BP	07033	27	12.8	PGJ13	C-6		2.68/68.1	0.42/10.7	500
889CVSU-BP	07018	27	12.8	PGJ13	C-6		2.68/68.1	0.42/10.7	500
893CVSU-BP	07035	37.5	12.8	PG13	C-6		2.68/68.1	0.42/10.7	500
894CVSU-BP	07043	37.5	12.8	PGJ13	C-6		2.68/68.1	0.42/10.7	500
896CVSU-BP	07001	37.5	12.8	PGJ13	C-6		2.68/68.1	0.42/10.7	500
899CVSU-BP	01206	37.5	12.8	PG13	C-6		2.68/68.1	0.42/10.7	1,900
H1042CVSU-BP	07680	42	13.2	PY20d	CC-8	840	3.17/80.5	0.47/11.8	775
H1042CVSU2	07062	42	13.2	PY20d	CC-8	840	3.17/80.5	0.47/11.8	775
885CVSU-BP	07013	50	12.8	PG13	C-6	1320	2.68/68.1	0.42/10.7	500
9006CVSU-BP	07677	55	12.8	P22d	C-8	1005	3.09/78.0	0.42/10.7	1,000
9006CVSU2	02434	55	12.8	P22d	C-8	1005	3.09/78.0	0.42/10.7	1,000
9006XSCVSU-BP	07674	55	12.8	P22d	C-8	1005	2.61/66.29	0.42/10.7	1,000
9006XSCVSU2	07673	55	12.8	P22d	C-8	1005	2.61/66.29	0.42/10.7	1,000
H1155CVSU-BP	07681	55	13.2	PGJ19-2	CC-8	1345	2.64/67	0.43/10.8	550
H1155CVSU2	07008	55	13.2	PGJ19-2	CC-8	1345	2.64/67	0.43/10.8	550
H11BCVSU-BP	07682	55	13.2	PGJY19-2	CC-8	1345	2.63/66.8	0.43/10.8	1,000
H11BCVSU2	07010	55	13.2	PGJY19-2	CC-8	1345	2.63/66.8	0.43/10.8	1,000
H155CVSU-BP	07683	55	12	P14.5s	C-8	1545	2.65/67.3	0.33/8.4	225

>>Continued on page 43



880 / 893 / 899 CVSu



881 / 896 CVSu



889 / 894 CVSu



885 CVSu



H155 CVSu



H1155 CVSu



Miniature Lamps (Alphanumeric)

Item	Order Code	Amps	Volts	Base	Filament	MOL in/mm	MOD in/mm	Life
577	42082	1.4	12.8	Double End Cap	C-8	1.72/43.7	0.62/15.8	1,000
577-BP	42080	1.4	12.8	Double End Cap	C-8	1.72/43.7	0.62/15.8	1,000
578	06699	0.78	12.8	Double End Cap	C-8	1.72/43.7	0.38/9.6	1,000
578-BP	06700	0.97	12.8	Double End Cap	C-8	1.72/43.7	0.38/9.6	1,000
579	06702	0.80	12.8	W2.1x9.5d	C-2R	1.49/37.9	0.62/15.8	200
579-BP	06703	0.80	12.8	W2.1x9.5d	C-2R	1.49/37.9	0.62/15.8	200
585	40759	0.04	28	W2.1x9.5d	C-2F	1.06/26.9	0.40/10.2	7,000
605	40826	0.5	6.15	E10	C-2R	1.07/27.2	0.59/15.0	15
623	40828	0.37	28	BA15s	2C-6	1.44/36.6	0.75/19.1	1,000
624	40829	0.37	28	BA15d	2C-6	1.44/36.6	0.75/19.1	1,000
631	40832	0.63	14	BA15s	C-6/C-6	1.44/36.6	0.75/19.1	1,000
631-BP	40833	0.63	14	BA15s	C-6/C-6	1.44/36.6	0.75/19.1	1,000
655	49620	0.20	28	W2.1x9.5d	C-2F	1.06/26.9	0.40/10.2	7,000
656	40836	0.06	28	W2.1x9.5d	C-2F	1.06/26.9	0.40/10.2	2,500
657	40837	0.08	28	W2.1x9.5d	C-2F	1.06/26.9	0.40/10.2	15,000
658	42272	0.08	14	W2.1x9.5d	C-2F	1.06/26.9	0.40/10.2	15,000
658-BP	42086	0.08	14	W2.1x9.5d	C-2F	1.06/26.9	0.40/10.2	15,000
680	40852	0.06	5	WL	C-2R	0.25/6.4	0.13/3.2	60,000
683	40856	0.06	5	WL	C-2R	0.25/6.4	0.13/3.2	25,000
685	40872	0.06	5	SX4s	C-2R	0.38/9.7	0.13/3.2	25,000
715	40884	0.115	5	WL	C-2R	0.25/6.4	0.13/3.2	40,000
718	81173	0.115	5	SX4s	C-2R	0.38/9.7	0.13/3.2	40,000
755	40932	0.15	6.3	BA9s	C-2R	1.19/30.2	0.43/11.0	20,000
755-BP	16052	0.15	6.3	BA9s	C-2R	1.19/30.2	0.43/11.0	20,000
756	40934	0.08	14	BA9s	C-2F	1.19/30.2	0.43/11.0	15,000
757	40936	0.08	28	BA9s	C-2F	1.19/30.2	0.40/10.2	15,000
757-BP	42362	0.08	28	BA9s	C-2F	1.19/30.2	0.40/10.2	15,000
778	41400	3.33	6	G4	C-6	1.05/26.7	0.38/9.6	100
787	41402	1.67	6	G4	C-6	1.00/25.4	0.30/7.6	100
788	41404	3.33	6	G4	C-6	1.00/25.4	0.30/7.6	100
789	41406	1.17	12	G4	C-6	1.05/26.7	0.38/9.6	200
795	44019	3.91	12.8	BA15s	C-6	2.50/63.5	0.48/12.2	200
795X	44021	3.91	12.8	BA15s	C-8	2.50/63.5	0.48/12.2	200
796	44023	2.73	12.8	BA15s	C-6	2.50/63.5	0.48/12.2	300
797	00447	3.91	12.8	G7.1	C-6	1.9/48.3	0.5/13	200
882	42100	0.35	12.8	B10d	C-6	1.18/30.0	0.72/18.3	2,000
891	42116	0.625	12.8	G4	C-6	1.20/30.5	0.32/8.1	800
895	41004	0.53	40	BA15d	CC-6	2.00/50.8	1.04/26.4	3,800
901	42141	0.31	12.8	W2.1x9.5d	C-2R	1.49/37.9	0.62/15.8	500
901A	43201	0.31	12.8	W2.1x9.5d	C-2R	1.49/37.9	0.62/15.8	500
901B	43204	0.31	12.8	W2.1x9.5d	C-2R	1.49/37.9	0.62/15.8	500
901-BP	42143	0.31	12.8	W2.1x9.5d	C-2R	1.49/37.9	0.62/15.8	500
901G	43207	0.31	12.8	W2.1x9.5d	C-2R	1.49/37.9	0.62/15.8	500
901R	43210	0.31	12.8	W2.1x9.5d	C-2R	1.49/37.9	0.62/15.8	500
904	41010	0.69	13.5	W2.1x9.5d	C-2F	1.49/37.9	0.62/15.8	5,000
904-BP	42206	0.69	13.5	W2.1x9.5d	C-2F	1.49/37.9	0.62/15.8	5,000
906	41012	0.69	13	W2.1x9.5d	C-2F	1.49/37.9	0.62/15.8	1,000
906A	01814	0.69	13	W2.1x9.5d	C-2F	1.49/37.9	0.62/15.8	1,000
906B	00358	0.69	13	W2.1x9.5d	C-2F	1.49/37.9	0.62/15.8	1,000
906-BP	42142	0.69	13	W2.1x9.5d	C-2F	1.49/37.9	0.62/15.8	1,000
906G	00356	0.69	13	W2.1x9.5d	C-2F	1.49/37.9	0.62/15.8	1,000
906P	06011	0.69	13	W2.1x9.5d	C-2F	1.49/37.9	0.62/15.8	1,000
906R	00357	0.69	13	W2.1x9.5d	C-2F	1.49/37.9	0.62/15.8	1,000