



Automotive & Miniature Lamps

EIKO's line of original equipment headlamps and miniature indicator and accent lamps were designed to meet or exceed the performance of your vehicle's original lamp. Manufactured to exacting standards, they feature top quality components and are guaranteed to perform like the original. Our metal-based lamps also feature an industry-first, nickel-plated brass base which prevents corrosion and ensures performance. Additionally, each and every lamp is quality tested before it leaves the factory.

CLEAR VISION®
Supreme

Clear Vision® Supreme High Performance Forward Lighting

Item	Order Code	Watts	Volts	Base	Filament	Lumens	MOL in/mm	MOD in/mm	Life
880CVSU-BP	07021	27	12.8	PG13	C-6		2.68/68.1	0.42/10.7	500
881CVSU-BP	07033	27	12.8	PGJ13	C-6		2.68/68.1	0.42/10.7	500
889CVSU-BP	07018	27	12.8	PGJ13	C-6		2.68/68.1	0.42/10.7	500
893CVSU-BP	07035	37.5	12.8	PG13	C-6		2.68/68.1	0.42/10.7	500
894CVSU-BP	07043	37.5	12.8	PGJ13	C-6		2.68/68.1	0.42/10.7	500
896CVSU-BP	07001	37.5	12.8	PGJ13	C-6		2.68/68.1	0.42/10.7	500
899CVSU-BP	01206	37.5	12.8	PG13	C-6		2.68/68.1	0.42/10.7	1,900
H1042CVSU-BP	07680	42	13.2	PY20d	CC-8	840	3.17/80.5	0.47/11.8	775
H1042CVSU2	07062	42	13.2	PY20d	CC-8	840	3.17/80.5	0.47/11.8	775
885CVSU-BP	07013	50	12.8	PG13	C-6	1320	2.68/68.1	0.42/10.7	500
9006CVSU-BP	07677	55	12.8	P22d	C-8	1005	3.09/78.0	0.42/10.7	1,000
9006CVSU2	02434	55	12.8	P22d	C-8	1005	3.09/78.0	0.42/10.7	1,000
9006XSCVSU-BP	07674	55	12.8	P22d	C-8	1005	2.61/66.29	0.42/10.7	1,000
9006XSCVSU2	07673	55	12.8	P22d	C-8	1005	2.61/66.29	0.42/10.7	1,000
H1155CVSU-BP	07681	55	13.2	PGJ19-2	CC-8	1345	2.64/67	0.43/10.8	550
H1155CVSU2	07008	55	13.2	PGJ19-2	CC-8	1345	2.64/67	0.43/10.8	550
H11BCVSU-BP	07682	55	13.2	PGJY19-2	CC-8	1345	2.63/66.8	0.43/10.8	1,000
H11BCVSU2	07010	55	13.2	PGJY19-2	CC-8	1345	2.63/66.8	0.43/10.8	1,000
H155CVSU-BP	07683	55	12	P14.5s	C-8	1545	2.65/67.3	0.33/8.4	225

>>Continued on page 43



880 / 893 / 899 CVSu



881 / 896 CVSu



889 / 894 CVSu



885 CVSu



H155 CVSu



H1155 CVSu



Miniature Lamps (Alphanumeric)

Item	Order Code	Amps	Volts	Base	Filament	MOL in/mm	MOD in/mm	Life
2185	00226	0.04	28	WL	C-2F	0.52/13.2	0.23/5.9	10,000
2187	40484	0.04	28	WL	C-2F	0.52/13.2	0.23/5.9	10,000
2200	40488	0.06	5	WL	C-2R	0.52/13.2	0.23/5.9	25,000
2232	42384	0.643	28	BA15s	CC-8	2.00/50.8	1.04/26.4	2,000
2233	42386	0.766	28	BA15s	CC-8	2.00/50.8	1.04/26.4	2,000
2357	40498	2.23/0.59	12.8/14	BAY15d	C-6/C-6	2.00/50.8	1.04/26.4	400 / 5000
2357A	42304	2.23/0.59	12.8/14	BAY15d	C-6/C-6	2.00/50.8	1.04/26.4	400 / 5000
2357A-BP	42234	2.23/0.59	12.8/14	BAY15d	C-6/C-6	2.00/50.8	1.04/26.4	400 / 5000
2357-BP	40499	2.23/0.59	12.8/14	BAY15d	C-6/C-6	2.00/50.8	1.04/26.4	400 / 5000
2357LL-BP	40329	2.23/0.59	12.8/14	BAY15d	C-6/C-6	2.00/50.8	1.04/26.4	800 / 10000
2357NA	40501	2.23/0.59	12.8/14	BAY15d	C-6/C-6	2.00/50.8	1.04/26.4	400 / 5000
2357NA-BP	40502	2.23/0.59	12.8/14	BAY15d	C-6/C-6	2.00/50.8	1.04/26.4	400 / 5000
2396	40504	2.23	12.8	BA15s	C-6	2.00/50.8	1.04/26.4	400
2396-BP	40633	2.23	12.8	BA15s	C-6	2.00/50.8	1.04/26.4	400
2397	42229	2.23/0.48	12.8/14	BAY15d	C-6/C-6	2.00/50.8	1.04/26.4	400 / 2000
2397-BP	42230	2.23/0.48	12.8/14	BAY15d	C-6/C-6	2.00/50.8	1.04/26.4	400 / 2000
2410X-1	50038	0.417	24	W2.1x9.5d	C-2V	1.06/26.9	0.40/10.2	10,000
2410X-2	50054	0.417	24	W2.1x9.5d	C-2F	1.53/38.9	0.62/15.8	3,000
2450X	50030	0.208	24	W2.1x9.5d	C-2V	1.06/26.9	0.40/10.2	500
2470X	50032	0.3	24	W2.1x9.5d	C-2V	1.06/26.9	0.40/10.2	12,000
2475X-1	50036	0.313	24	W2.1x9.5d	C-2V	1.06/26.9	0.40/10.2	10,000
2504	07861	2.00	12	PG20-7	C-8Z	1.42/36	.71/18	750
2721	42231	0.1	12	W2x4.6d	C-2V	0.80/20.3	0.20/5.1	1,000
2721-BP	40635	0.1	12	W2x4.6d	C-2V	0.80/20.3	0.20/5.1	1,000
2721MF	05259	0.1	12	B8.5d	C-2V	0.925/23.5	0.20/5.1	1,000
2721MF-BP	49831	0.1	12	B8.5d	C-2V	0.925/23.5	0.20/5.1	1,000
2723	01044	0.19	12	W2x4.6d	C-2V	0.80/20.3	0.20/5.1	1,100
2723-BP	40638	0.19	12	W2x4.6d	C-2V	0.80/20.3	0.20/5.1	1,100
2741	42223	0.05	24	W2x4.6d	C-2V	0.80/20.3	0.20/5.1	1,000
2741MF	00198	0.05	24	B8.5d	C-2V	0.925/23.5	0.20/5.1	1,000
2821	42232	0.25	12	W2.1x9.5d	C-2V	1.06/26.9	0.40/10.2	1,000
2821-BP	42233	0.25	12	W2.1x9.5d	C-2V	1.06/26.9	0.40/10.2	1,000
2825	40637	0.4	12	W2.1x9.5d	C-2V	1.06/26.9	0.40/10.2	750
2825-BP	42235	0.4	12	W2.1x9.5d	C-2R	1.06/26.9	0.40/10.2	750
2827	06379	0.4	12	W2.1x9.5d	C-2R	1.06/26.9	0.40/10.2	300
2827-BP	06380	0.4	12	W2.1x9.5d	C-2R	1.06/26.9	0.40/10.2	300
2841	49053	0.125	24	W2.1x9.5d	C-2V	1.06/26.9	0.40/10.2	1,000
2860X	50042	0.214	28	W2.1x9.5d	C-2V	1.06/26.9	0.40/10.2	1,000
3047K	06383	1.59/0.48	12.8/14	W2.5x16q	C-6/C-6	2.09/53.1	1.04/26.4	2000/10000
3047K-BP	06384	1.59/0.48	12.8/14	W2.5x16q	C-6/C-6	2.09/53.1	1.04/26.4	2000/10000
3057	40600	2.1/0.48	12.8/14	W2.5x16q	C-6/C-6	2.09/53.1	1.04/26.4	1200/5000
3057A	42621	2.1/0.48	12.8/14	W2.5x16q	C-6/C-6	2.09/53.1	1.04/26.4	1200/5000
3057A-BP	42622	2.1/0.48	12.8/14	W2.5x16q	C-6/C-6	2.09/53.1	1.04/26.4	1200/5000
3057-BP	40601	2.1/0.48	12.8/14	W2.5x16q	C-6/C-6	2.09/53.1	1.04/26.4	1200/5000
3057K	42600	2.1/0.48	12.8/14	W2.5x16q	C-6/C-6	2.09/53.1	1.04/26.4	2000/10000
3057K-BP	42601	2.1/0.48	12.8/14	W2.5x16q	C-6/C-6	2.09/53.1	1.04/26.4	2000/10000
3057NA	40603	2.1/0.48	12.8/14	W2.5x16q	C-6/C-6	2.09/53.1	1.04/26.4	1200/5000
3057NA-BP	40604	2.1/0.48	12.8/14	W2.5x16q	C-6/C-6	2.09/53.1	1.04/26.4	1200/5000
3155	42288	1.6	12.8	W2.5x16d	C-6	2.09/53.1	1.04/26.4	1,500
3155-BP	42186	1.6	12.8	W2.5x16d	C-6	2.09/53.1	1.04/26.4	1,500
3155K	49718	1.44	12.8	W2.5x16d	C-6	2.09/53.1	1.04/26.4	2,000
3156	42292	2.1	12.8	W2.5x16d	C-6	2.09/53.1	1.04/26.4	1,200
3156A	49035	2.1	12.8	W2.5x16d	C-6	2.09/53.1	1.04/26.4	1,200
3156-BP	42188	2.1	12.8	W2.5x16d	C-6	2.09/53.1	1.04/26.4	1,200
3156K	42603	2.1	12.8	W2.5x16d	C-6	2.09/53.1	1.04/26.4	2,000
3156K-BP	42604	2.1	12.8	W2.5x16d	C-6	2.09/53.1	1.04/26.4	2,000