



Halogen Lamps

EiKO's commercial grade Halogen Lamps feature high-grade, heavy-gauge glass, high output halogen burners, premium gas mixtures, quality reflector coatings, linear beam patterns, and superior construction quality. The result? A reliable, high performance product that lowers your overall cost. Halogen lamps provide a whiter, brighter light that saves up to 30% in energy costs when compared to incandescent lamps.

EiKON™ Energy Efficient Halogen IR PAR30

Order Code	Item	W	V	Base	Fil	Lm	MOL in/mm	MOD in/mm	Bm	Life/Hrs	Photo #
08206	IR53PAR30/FL	53	120	E26	CC-8	1050	3.66/93	3.74/95	35	4,000	1
08205	IR53PAR30/NFL	53	120	E26	CC-8	1050	3.66/93	3.74/95	25	4,000	1
08204	IR53PAR30/SP	53	120	E26	CC-8	1050	3.66/93	3.74/95	10	4,000	1

EiKON™ Energy Efficient Halogen IR PAR30LN

Order Code	Item	W	V	Base	Fil	Lm	MOL in/mm	MOD in/mm	Bm	Life/Hrs	Photo #
08208	IR53PAR30LN/NFL	53	120	E26	CC-8	930	4.76/121	3.74/95	25	4,000	2
08209	IR53PAR30LN/WFL	53	120	E26	CC-8	930	4.76/121	3.74/95	50	4,000	2
08207	IR53PAR30LN/SP*	53	120	E26	CC-8	930	4.76/121	3.74/95	10	4,000	2

EiKON™ Energy Efficient Halogen IR PAR38

Order Code	Item	W	V	Base	Fil	Lm	MOL in/mm	MOD in/mm	Bm	Life/Hrs	Photo #
08210	IR53PAR38/FL	53	120	E26	CC-8	960	5.51/140	4.80/122	25	4,000	3
08211	IR71PAR38/FL	71	120	E26	CC-8	1370	5.51/140	4.80/122	25	4,000	3
08212	IR71PAR38/SP*	71	120	E26	CC-8	1370	5.51/140	4.80/122	10	4,000	3



Order Code	Item	W	V	Base	Fil	Lm	MOL in/mm	MOD in/mm	Life/Hrs	Photo #
15268	Q250CL/MC-130V	250	130	E11	CC-8	5000	3.15/80.0	0.52/13.0	2,000	16
49607	Q250DC-120V	250	120	BA15d	CC-8	4700	3.15/80.0	0.55/14.0	2,000	16
15266	Q250DC-130V*	250	130	BA15d	CC-8	4800	3.00/76.2	0.52/13.0	2,000	16
49608	Q250MC-120V	250	120	E11	CC-8	4800	3.19/81.0	0.52/13.0	2,000	16
15270	Q250MC-130V	250	130	E11	CC-8	4800	3.19/81.0	0.52/13.0	2,000	16
49612	Q500/MC-120V	500	120	E11	CC-8	8800	3.75/95.3	0.52/13.0	1,700	16
49614	Q500/MC-130V	500	130	E11	CC-8	8800	3.75/95.3	0.52/13.0	1,700	16
15282	Q500CL/DC-120V	500	120	BA15d	CC-8	8800	3.75/95.3	0.59/15.0	1,700	16
49613	Q500CL/MC-120V	500	120	E11	CC-8	8800	3.75/95.3	0.55/14.0	1,700	16
49615	Q500CL/MC-130V	500	130	E11	CC-8	8800	3.75/95.3	0.52/13.0	1,700	16

Double Ended Halogen Lamps

Order Code	Item	W	V	Base	Fil	Lm	MOL in/mm	MOD in/mm	Life/Hrs	Photo #
15161	Q150T3/CL/120V	150	120	R7s	CC-8	2200	4.69/119.1	0.40/10.0	2,000	17
15162	Q250T3/CL/120V	250	120	R7s	C-8	3500	4.69/119.1	0.40/10.0	2,000	17
15164	Q300T3/CL/120V	300	120	R7s	C-8	4800	4.69/119.1	0.40/10.0	2,000	17
15166	Q300T3/CL/130V	300	130	R7s	C-8	4800	4.69/119.1	0.40/10.0	2,000	17
15168	Q300T3/CL/220V	300	220	R7s	C-8	4500	4.69/119.1	0.40/10.0	2,000	17
00196	Q300T3/CL/240V	300	240	R7s	C-8	4500	4.69/119.1	0.40/10.0	2,000	17
15170	Q500T3/CL/120V	500	120	R7s	C-8	10000	4.69/119.1	0.40/10.0	2,000	17
15172	Q500T3/CL/130V	500	130	R7s	C-8	9500	4.69/119.1	0.40/10.0	2,000	17
15174	Q500T3/CL/220V	500	220	R7s	C-8	9000	4.69/119.1	0.40/10.0	2,000	17
15176	Q500T3/CL/240V	500	240	R7s	C-8	9000	4.69/119.1	0.40/10.0	2,000	17
49568	Q750T3/CL/120V	750	120	R7s	C-8	15000	7.50/190.5	0.40/10.0	2,000	17
15180	Q750T3/CL/240V	750	240	R7s	C-8	16500	7.50/190.5	0.40/10.0	2,000	17
49569	Q1000T3/CL/120V	1000	120	R7s	C-8	22000	10.06/255.6	0.40/10.0	2,000	17
15184	Q1000T3/CL/240V	1000	240	R7s	C-8	21000	10.06/255.6	0.40/10.0	2,000	17
15186	Q1000T3/CL/277V	1000	277	R7s	C-8	22000	10.06/255.6	0.40/10.0	2,000	17
49570	Q1500T3/CL/120V	1500	120	R7s	CC-8	33000	10.06/255.6	0.40/10.0	2,000	17
15188	Q1500T3/CL/208V	1500	208	R7s	C-8	32000	10.06/255.6	0.40/10.0	2,000	17
15190	Q1500T3/CL/220V	1500	220	R7s	CC-8	32000	10.06/255.6	0.40/10.0	2,000	17
15192	Q1500T3/CL/240V	1500	240	R7s	CC-8	32000	10.06/255.6	0.40/10.0	2,000	17
15194	Q1500T3/CL/277V	1500	277	R7s	CC-8	34000	10.06/255.6	0.40/10.0	2,000	17

Double Ended Short Halogen Lamps

Order Code	Item	W	V	Base	Fil	Lm	MOL in/mm	MOD in/mm	Life/Hrs	Photo #
15200	Q100W/S120V	100	120	R7s	C-8	1300	3.15/80.0	0.315/8.0	2,000	17
15202	Q100W/S130V	100	130	R7s	C-8	1300	3.15/80.0	0.315/8.0	2,000	17
15206	Q150W/S120V	150	120	R7s	C-8	2200	3.15/80.0	0.344/8.74	2,000	17
15208	Q150W/S130V	150	130	R7s	C-8	2200	3.15/80.0	0.344/8.74	2,000	17
15211	Q200W/S120V	200	120	R7s	C-8	3000	3.15/80.0	0.344/8.74	2,000	17
15213	Q200W/S130V	200	130	R7s	C-8	3000	3.15/80.0	0.344/8.74	2,000	17
15209	Q200W/S220V	200	220	R7s	CC-8	3000	3.15/80.0	0.344/8.74	2,000	17
49571	Q250W/S120V	250	120	R7s	CC-8	3500	3.15/80.0	0.360/9.13	2,000	17
00019	Q300W/S120V	300	120	R7s	CC-8	4100	3.15/80.0	0.360/9.13	2,000	17
15216	Q300W/S130V	300	130	R7s	CC-8	4100	3.15/80.0	0.360/9.13	2,000	17
15221	Q400W/S130V*	400	130	R7s	C-8	5500	3.15/80.0	0.406/10.32	2,000	17