

## C-Shaped Incandescent Lamps

| Order Code | Item         | W  | V   | Shape | Base  | Fil  | Lm  | MOL in/mm | MOD in/mm | Life/Hrs | Photo # |
|------------|--------------|----|-----|-------|-------|------|-----|-----------|-----------|----------|---------|
| 40353      | 4C7/120V     | 4  | 120 | C-7   | E12   | C-7A | 20  | 2.30/58.4 | 0.88/22.3 | 3,000    | 3       |
| 40351      | 4C7/130V     | 4  | 130 | C-7   | E12   | C-7A | 15  | 2.30/58.4 | 0.88/22.3 | 3,000    | 3       |
| 40874      | 7C7/120V     | 7  | 120 | C-7   | E12   | C-7A | 37  | 2.30/58.4 | 0.88/22.3 | 3,000    | 3       |
| 40875      | 7C7/130V     | 7  | 130 | C-7   | E12   | C-7A | 35  | 2.30/58.4 | 0.88/22.3 | 3,000    | 3       |
| 44318      | 7C7/130V-W   | 7  | 130 | C-7   | E12   | C-7A | n/a | 2.30/58.4 | 0.88/22.3 | 3,000    | 3       |
| 01709      | 7C9-120V-INT | 7  | 120 | C-9   | E17   | C-5A | 45  | 3.9/99    | 1.15/29.2 | 3,000    | 3       |
| 40073      | 10C7/120V    | 10 | 120 | C-7   | E12   | C-7A | 64  | 2.30/58.4 | 0.88/22.3 | 5000+    | 3       |
| 40154      | 10C7DC/120V  | 10 | 120 | C-7   | BA15d | C-7A | 64  | 2.13/54.1 | 0.88/22.3 | 5000+    | 3       |

## R&amp;BR Incandescent Lamps

| Order Code | Item           | W  | V   | Shape | Base | Fil  | Lm  | MOL in/mm  | Life/Hrs         | Photo # |
|------------|----------------|----|-----|-------|------|------|-----|------------|------------------|---------|
| 49792      | 30R20/FL-130V  | 30 | 130 | R-20  | E26  | CC-6 | 245 | 3.94/100   | 5000 Hrs at 120v | 4       |
| 49797      | 45BR30/FL-120V | 45 | 120 | BR-30 | E26  | CC-6 | 390 | 5.38/136.7 | 2,000            | 5       |
| 05986      | 45R20/FL-120V  | 45 | 120 | R-20  | E26  | CC-6 | 360 | 3.94/100   | 2,000            | 4       |
| 05987      | 45R20/FL-130V  | 45 | 130 | R-20  | E26  | CC-6 | 340 | 3.94/100   | 5000 Hrs at 120v | 4       |
| 49798      | 65BR30/FL-120V | 65 | 120 | BR-30 | E26  | CC-6 | 620 | 5.38/136.7 | 2,000            | 5       |
| 49799      | 65BR30/FL-130V | 65 | 130 | BR-30 | E26  | CC-6 | 620 | 5.38/136.7 | 5000 Hrs at 120v | 5       |
| 49811      | 65BR30/SP-120V | 65 | 120 | BR-30 | E26  | CC-6 | 620 | 5.38/136.7 | 2,000            | 5       |
| 49800      | 65BR30/SP-130V | 65 | 130 | BR-30 | E26  | CC-6 | 620 | 5.38/136.7 | 5000 Hrs at 120v | 5       |
| 49801      | 65BR40/FL-120V | 65 | 120 | BR-40 | E26  | CC-6 | 620 | 6.56/166.6 | 2,000            | 6       |
| 49802      | 65BR40/FL-130V | 65 | 130 | BR-40 | E26  | CC-6 | 620 | 6.56/166.6 | 5000 Hrs at 120v | 6       |

## S-Shaped Incandescent Lamps

| Order Code | Item         | W | V   | Shape | Base  | Fil  | Lm    | MOL in/mm | MOD in/mm | Life/Hrs | Photo # |
|------------|--------------|---|-----|-------|-------|------|-------|-----------|-----------|----------|---------|
| 40552      | 3S6/5-120V   | 3 | 120 | S-6   | E12   | C-7A | 11.31 | 1.88/47.8 | 0.75/19.1 | 1,500    | 7       |
| 40554      | 3S6/5-130V   | 3 | 130 | S-6   | E12   | C-7A | 11.31 | 1.88/47.8 | 0.75/19.1 | 1,500    | 7       |
| 40556      | 3S6/5DC-120V | 3 | 120 | S-6   | BA15d | C-7A | 11.31 | 1.82/46.2 | 0.75/19.1 | 3,000    | 7       |
| 40786      | 6S6/120V     | 6 | 120 | S-6   | E12   | C-7A | 39    | 1.88/47.8 | 0.75/19.1 | 1,500    | 7       |
| 40784      | 6S6/12V      | 6 | 12  | S-6   | E12   | C-6  | 48    | 1.88/47.8 | 0.75/19.1 | 1,500    | 7       |
| 40788      | 6S6/130V     | 6 | 130 | S-6   | E12   | C-7A | 38    | 1.88/47.8 | 0.75/19.1 | 1,500    | 7       |
| 40789      | 6S6/145V     | 6 | 145 | S-6   | E12   | C-7A | 17.60 | 1.88/47.8 | 0.75/19.1 | 1,500    | 7       |
| 40790      | 6S6/155V     | 6 | 155 | S-6   | E12   | C-7A | 33    | 1.88/47.8 | 0.75/19.1 | 1,500    | 7       |
| 49717      | 6S6/18V      | 6 | 18  | S-6   | E12   | C-6  | 50    | 1.88/47.8 | 0.75/19.1 | 1,500    | 7       |
| 40791      | 6S6/230V     | 6 | 230 | S-6   | E12   | C-7A | 11.31 | 1.88/47.8 | 0.75/19.1 | 1,500    | 7       |
| 40792      | 6S6/24V      | 6 | 24  | S-6   | E12   | C-6  | 53    | 1.88/47.8 | 0.75/19.1 | 1,500    | 7       |
| 40794      | 6S6/30V      | 6 | 30  | S-6   | E12   | C-6  | 52    | 1.88/47.8 | 0.75/19.1 | 1,500    | 7       |
| 40796      | 6S6/48V      | 6 | 48  | S-6   | E12   | C-6  | 47    | 1.88/47.8 | 0.75/19.1 | 1,500    | 7       |
| 40800      | 6S6/60V      | 6 | 60  | S-6   | E12   | C-7A | 43    | 1.88/47.8 | 0.75/19.1 | 1,500    | 7       |
| 40798      | 6S6/6V       | 6 | 6   | S-6   | E12   | C-6  | 54    | 1.88/47.8 | 0.75/19.1 | 1,500    | 7       |
| 40804      | 6S6DC/120V   | 6 | 120 | S-6   | BA15d | C-7A | 39    | 1.82/46.2 | 0.75/19.1 | 1,500    | 7       |
| 40802      | 6S6DC/12V    | 6 | 12  | S-6   | BA15d | C-6  | 48    | 1.82/46.2 | 0.75/19.1 | 1,500    | 7       |
| 40806      | 6S6DC/130V   | 6 | 130 | S-6   | BA15d | C-7A | 38    | 1.82/46.2 | 0.75/19.1 | 1,500    | 7       |

Continued on next page &gt;&gt;&gt;



3



4



5



6



7



## Miniature Lamps

EIKO offers one of the widest lines of miniature lamps in the industry. Featuring quality construction with durable design, our lamps meet or exceed SAE and/or ANSI specifications for lumen output and lifetime hours and are known for their long-term reliability. Our in-house testing facilities ensure product quality. Available in traditional incandescent lamps or energy-efficient LED lamps that feature extraordinary long life.

### LED Miniature Lamps

| Order Code | Item                  | Volts        | Base                            | Bulb    | MOL in/ mm | MOD in/ mm | Lumens   | Life/Hrs |
|------------|-----------------------|--------------|---------------------------------|---------|------------|------------|----------|----------|
| 02697      | LED-24-MF-R*          | 24~28 VAC/DC | Midget Flanged (SX6s)           | T-1 3/4 | 0.63/16    | 0.24/6     | 0.7      | 30,000   |
| 02698      | LED-24-MF-W           | 24~28 VAC/DC | Midget Flanged (SX6s)           | T-1 3/4 | 0.63/16    | 0.24/6     | 3.2      | 30,000   |
| 02702      | LED-24-MG-W           | 24~28 VAC/DC | Midget Grooved (S5.7s)          | T-1 3/4 | 0.63/16    | 0.24/6     | 1.1      | 30,000   |
| 02688      | LED-14-BA9S-R         | 14 VAC/DC    | Miniature Bayonet (BA9s)        | T-3 1/4 | 1.0/25     | 0.40/10    | 0.75     | 30,000   |
| 02687      | LED-14-BA9S-G         | 14 VAC/DC    | Miniature Bayonet (BA9s)        | T-3 1/4 | 1.0/25     | 0.40/10    | 1.5      | 30,000   |
| 02689      | LED-14-BA9S-W         | 14 VAC/DC    | Miniature Bayonet (BA9s)        | T-3 1/4 | 1.0/25     | 0.40/10    | 2.4      | 30,000   |
| 02694      | LED-24-BA9S-R         | 24~28 VAC/DC | Miniature Bayonet (BA9s)        | T-3 1/4 | 1.0/25     | 0.40/10    | 0.7      | 30,000   |
| 02696      | LED-24-BA9S-Y         | 24~28 VAC/DC | Miniature Bayonet (BA9s)        | T-3 1/4 | 1.0/25     | 0.40/10    | 0.6      | 30,000   |
| 02693      | LED-24-BA9S-G         | 24~28 VAC/DC | Miniature Bayonet (BA9s)        | T-3 1/4 | 1.0/25     | 0.40/10    | 1.5      | 30,000   |
| 02695      | LED-24-BA9S-W         | 24~28 VAC/DC | Miniature Bayonet (BA9s)        | T-3 1/4 | 1.0/25     | 0.40/10    | 2.4      | 30,000   |
| 02679      | LED-120-MB-R          | 110~130 VAC  | Miniature Bayonet (BA9s)        | T-3 1/4 | 1.0/25     | 0.40/10    | 0.2      | 30,000   |
| 02682      | LED-120-MB-Y          | 110~130 VAC  | Miniature Bayonet (BA9s)        | T-3 1/4 | 1.0/25     | 0.40/10    | 0.2      | 30,000   |
| 02678      | LED-120-MB-G          | 110~130 VAC  | Miniature Bayonet (BA9s)        | T-3 1/4 | 1.0/25     | 0.40/10    | 0.5      | 30,000   |
| 02681      | LED-120-MB-W          | 110~130 VAC  | Miniature Bayonet (BA9s)        | T-3 1/4 | 1.0/25     | 0.40/10    | 0.6      | 30,000   |
| 02705      | LED-24-PSB-R          | 24~28 VAC/DC | Slide Base 5 (TS5)              | T-2     | 1.1/28     | 0.27/6.8   | 0.4      | 30,000   |
| 02706      | LED-24-PSB-W          | 24~28 VAC/DC | Slide Base 5 (TS5)              | T-2     | 1.1/28     | 0.27/6.8   | 1.1      | 30,000   |
| 02707      | LED-24-PSB-Y          | 24~28 VAC/DC | Slide Base 5 (TS5)              | T-2     | 1.1/28     | 0.27/6.8   | 0.4      | 30,000   |
| 02704      | LED-24-PSB-G          | 24~28 VAC/DC | Slide Base 5 (TS5)              | T-2     | 1.1/28     | 0.27/6.8   | 0.9      | 30,000   |
| 02684      | LED-120-PSB-R         | 110~130 VAC  | Slide Base 5 (TS5)              | T-2     | 1.1/28     | 0.27/6.8   | 0.2      | 30,000   |
| 02686      | LED-120-PSB-Y         | 110~130 VAC  | Slide Base 5 (TS5)              | T-2     | 1.1/28     | 0.27/6.8   | 0.2      | 30,000   |
| 02683      | LED-120-PSB-G         | 110~130 VAC  | Slide Base 5 (TS5)              | T-2     | 1.1/28     | 0.27/6.8   | 0.6      | 30,000   |
| 02685      | LED-120-PSB-W         | 110~130 VAC  | Slide Base 5 (TS5)              | T-2     | 1.1/28     | 0.27/6.8   | 0.9      | 30,000   |
| 02691      | LED-14-T1.75 WEDGE-W  | 14 VAC/DC    | Sub-Miniature Wedge (W2.1x4.6d) | T-1 3/4 | 0.77/19.4  | 0.22/5.5   | 1.1      | 30,000   |
| 02709      | LED-24-T1.75 WEDGE-R* | 24~28 VAC/DC | Sub-Miniature Wedge (W2.1x4.6d) | T-1 3/4 | 0.77/19.4  | 0.22/5.5   | 0.1      | 30,000   |
| 02711      | LED-24-T1.75 WEDGE-W  | 24~28 VAC/DC | Sub-Miniature Wedge (W2.1x4.6d) | T-1 3/4 | 0.77/19.4  | 0.22/5.5   | 1.1      | 30,000   |
| 02712      | LED-24-T1.75 WEDGE-Y* | 24~28 VAC/DC | Sub-Miniature Wedge (W2.1x4.6d) | T-1 3/4 | 0.77/19.4  | 0.22/5.5   | .3       | 30,000   |
| 05394      | LED-12-SCBAY-W        | 12 VAC/DC    | SC Bayonet (BA15s)              | S-8     | 1.28/32.6  | 0.73/18.5  | 21.6     | 10,000   |
| 05379      | LED-12-DCBAY-W        | 12 VAC/DC    | DC Index Bayonet (BAY15d)       | S-8     | 1.81/46    | 1.0/25     | 21.6/7.8 | 10,000   |

Continued on next page >>>

# Miniature

| Order Code | Item       | Volts     | Amps      | Base                                     | Bulb    | Filament | MOL in/mm | MOD in/mm | Lumens | Life/Hrs  |
|------------|------------|-----------|-----------|------------------------------------------|---------|----------|-----------|-----------|--------|-----------|
| 40672      | 385        | 28        | 0.04      | Midget Flanged (SX6s)                    | T-1 3/4 | C-2F     | 0.63/16.0 | 0.23/5.9  | 1.89   | 20,000    |
| 40674      | 386        | 14        | 0.08      | Midget Grooved (S5.7s)                   | T-1 3/4 | C-2F     | 0.63/16.0 | 0.23/5.9  | 3.77   | 40,000    |
| 40678      | 387        | 28        | 0.04      | Midget Flanged (SX6s)                    | T-1 3/4 | C-2F     | 0.63/16.0 | 0.23/5.9  | 3.77   | 10,000    |
| 40680      | 388        | 28        | 0.04      | Midget Grooved (S5.7s)                   | T-1 3/4 | C-2F     | 0.63/16.0 | 0.23/5.9  | 3.77   | 25,000    |
| 40686      | 394        | 12        | 0.04      | Midget Flanged (SX6s)                    | T-1 3/4 | C-2F     | 0.63/16.0 | 0.23/5.9  | 1.51   | 20,000    |
| 40692      | 399        | 28        | 0.04      | Midget Screw (E5)                        | T-1 3/4 | C-2F     | 0.72/18.3 | 0.23/5.9  | 3.77   | 7,000     |
| 40696      | 400        | 28        | 0.1       | Miniature Wedge (W2.1x9.5d)              | T-3 1/4 | C-2F     | 1.06/26.9 | 0.40/10.2 | 20.11  | 1,000     |
| 40012      | A3C        | 110       | 0.0018    | Wire Leads (WL) (2" Leads)               | T-2     | Neon     | 0.75/19.1 | 0.25/6.4  |        | 25,000    |
| 40720      | 455        | 6.5       | 0.5       | Miniature Bayonet (BA9s)                 | G-4 1/2 | C-2R     | 1.07/27.2 | 0.59/15.0 | 23.88  | 500       |
| 40464      | 2114       | 6         | 0.06      | Wire Leads (WL)                          | T-1 1/4 | C-2R     | 0.46/11.7 | 0.17/4.3  | 1.63   | 3,000     |
| 41704      | 77A/S8     | 12        | 0.77      | Single Contact Prefocus Flanged (P15s30) | S-8     | C-8S     | 2.09/53.1 | 1.04/26.4 | 120    | 500       |
| 44326      | 56         | 5         | 0.115     | Sub-Miniature Wedge (W2.1x4.9d)          | T-1 3/4 | C-2R     | 0.80/20.3 | 0.23/5.9  | 1.89   | 20,000    |
| 40468      | 2162       | 14        | 0.1       | Wire Leads (WL)                          | T-1 3/4 | C-2F     | 0.52/13.2 | 0.23/5.9  | 6.29   | 10,000    |
| 40470      | 2174       | 12        | 0.04      | Wire Leads (WL)                          | T-1 3/4 | C-2F     | 0.52/13.2 | 0.23/5.9  | 1.26   | 10,000    |
| 40472      | 2176       | 24        | 0.05      | Wire Leads (WL)                          | T-1 3/4 | C-2F     | 0.52/13.2 | 0.23/5.9  | 6.29   | 1,000     |
| 40478      | 2182       | 14        | 0.08      | Wire Leads (WL)                          | T-1 3/4 | C-2F     | 0.52/13.2 | 0.23/5.9  | 3.77   | 40,000    |
| 40484      | 2187       | 28        | 0.04      | Wire Leads (WL)                          | T-1 3/4 | C-2F     | 0.52/13.2 | 0.23/5.9  | 3.77   | 10,000    |
| 40488      | 2200       | 5         | 0.06      | Wire Leads (WL)                          | T-1 3/4 | C-2R     | 0.52/13.2 | 0.23/5.9  | 0.63   | 25,000    |
| 42384      | 2232       | 28        | 0.643     | SC Bayonet (BA15s)                       | S-8     | CC-8     | 2.00/50.8 | 1.04/26.4 | 225    | 2,000     |
| 42386      | 2233       | 28        | 0.766     | SC Bayonet (BA15s)                       | S-8     | CC-8     | 2.00/50.8 | 1.04/26.4 | 265    | 2,000     |
| 42231      | 2721       | 12        | 0.1       | Sub-Miniature Wedge (W2x4.6d)            | T-1 1/2 | C-2V     | 0.80/20.3 | 0.20/5.1  | 6.03   | 1,000     |
| 40637      | 2825       | 13.5      | 0.4       | Miniature Wedge (W2.1x9.5d)              | T-3 1/4 | C-2V     | 1.06/26.9 | 0.40/10.2 | 50     | 750       |
| 40114      | PR7        | 3.7       | 0.3       | SC Miniature Flanged (P13.5s)            | B-3 1/2 | C-2R     | 1.25/31.8 | 0.45/11.5 | 11.31  | 30        |
| 40084      | PR12       | 5.95      | 0.5       | SC Miniature Flanged (P13.5s)            | B-3 1/2 | C-2R     | 1.25/31.8 | 0.45/11.5 | 38     | 15        |
| 40086      | PR13       | 4.75      | 0.5       | SC Miniature Flanged (P13.5s)            | B-3 1/2 | C-2R     | 1.25/31.8 | 0.45/11.5 | 28     | 15        |
| 40090      | PR15       | 4.82      | 0.5       | SC Miniature Flanged (P13.5s)            | B-3 1/2 | C-2R     | 1.25/31.8 | 0.45/11.5 | 25     | 30        |
| 40092      | PR16       | 12.5      | 0.25      | SC Miniature Flanged (P13.5s)            | B-3 1/2 | C-2R     | 1.25/31.8 | 0.45/11.5 | 34     | 50        |
| 40096      | PR18       | 7.2       | 0.55      | SC Miniature Flanged (P13.5s)            | B-3 1/2 | C-2R     | 1.25/31.8 | 0.45/11.5 | 69     | 3         |
| 40102      | PR20       | 8.63      | 0.5       | SC Miniature Flanged (P13.5s)            | B-3 1/2 | C-2R     | 1.25/31.8 | 0.45/11.5 | 63     | 15        |
| 44011      | P21/5W*    | 13.5/13.5 | 1.86/0.44 | DC Index Bayonet (BAY15d)                | S-8     | C-6/C-6  | 2.06/52.5 | 1.05/26.5 | 440/35 | 300/2,000 |
| 50114      | JF02XE     | 6         | 0.833     | Rigid Loop (RGLP)                        | T-3 1/4 | C-8      | 1.72/43.7 | 0.40/10.0 | 55     | 20,000    |
| 40106      | PR30       | 3.75      | 0.86      | SC Miniature Flanged (P13.5s)            | B-3 1/2 | C-2R     | 1.25/31.8 | 0.45/11.5 | 28     | 40        |
| 40446      | 2          | 5         | 0.021     | Wire Leads (WL)                          | T-3/4   | C-2R     | 0.20/5.1  | 0.09/2.3  | 0.38   | 10,000    |
| 50118      | JF03XE*    | 12        | 0.417     | Rigid Loop (RGLP)                        | T-3 1/4 | C-8      | 1.72/43.7 | 0.40/10.0 | 60     | 3,000     |
| 40784      | 6S6/12V    | 12        | 0.5       | Candelabra Screw (E12)                   | S-6     | C-6      | 1.88/47.8 | 0.75/19.1 | 48     | 1,500     |
| 40792      | 6S6/24V    | 24        | 0.25      | Candelabra Screw (E12)                   | S-6     | C-6      | 1.88/47.8 | 0.75/19.1 | 53     | 1,500     |
| 40794      | 6S6/30V    | 30        | 0.2       | Candelabra Screw (E12)                   | S-6     | C-6      | 1.88/47.8 | 0.75/19.1 | 52     | 1,500     |
| 40796      | 6S6/48V    | 48        | 0.125     | Candelabra Screw (E12)                   | S-6     | C-6      | 1.88/47.8 | 0.75/19.1 | 47     | 1,500     |
| 40800      | 6S6/60V    | 60        | 0.1       | Candelabra Screw (E12)                   | S-6     | C-7A     | 1.88/47.8 | 0.75/19.1 | 43     | 1,500     |
| 40786      | 6S6/120V   | 120       | 0.05      | Candelabra Screw (E12)                   | S-6     | C-7A     | 1.88/47.8 | 0.75/19.1 | 39     | 1,500     |
| 40790      | 6S6/155V   | 155       | 0.039     | Candelabra Screw (E12)                   | S-6     | C-7A     | 1.88/47.8 | 0.75/19.1 | 33     | 1,500     |
| 40791      | 6S6/230V   | 230       | 0.026     | Candelabra Screw (E12)                   | S-6     | C-7A     | 1.88/47.8 | 0.75/19.1 | 11.31  | 1,500     |
| 43004      | 15T7N-130V | 130       | 0.12      | Intermediate Screw (E17)                 | T-7     | C-7A     | 2.25/57.2 | 0.89/22.6 | 90     | 1,500     |
| 40218      | 12ESB5*    | 12        | 0.04      | Slide Base 5 (TS5)                       | T-2     | C-2V     | 0.92/23.4 | 0.27/6.9  |        | 7,500     |
| 40220      | 12MB       | 12        | 0.17      | Miniature Bayonet (BA9s)                 | T-2 1/2 | C-2F     | 1.19/30.2 | 0.33/8.4  | 4.40   | 12,000    |
| 40222      | 12PSB5     | 12        | 0.17      | Slide Base 5 (TS5)                       | T-2     | C-2F     | 1.11/28.2 | 0.27/6.9  |        | 12,000    |

Continued on next page >>>