



Miniature Lamps

EIKO offers one of the widest lines of miniature lamps in the industry. Featuring quality construction with durable design, our lamps meet or exceed SAE and/or ANSI specifications for lumen output and lifetime hours and are known for their long-term reliability. Our in-house testing facilities ensure product quality. Available in traditional incandescent lamps or energy-efficient LED lamps that feature extraordinary long life.

LED Miniature Lamps

Order Code	Item	Volts	Base	Bulb	MOL in/ mm	MOD in/ mm	Lumens	Life/Hrs
02697	LED-24-MF-R*	24~28 VAC/DC	Midget Flanged (SX6s)	T-1 3/4	0.63/16	0.24/6	0.7	30,000
02698	LED-24-MF-W	24~28 VAC/DC	Midget Flanged (SX6s)	T-1 3/4	0.63/16	0.24/6	3.2	30,000
02702	LED-24-MG-W	24~28 VAC/DC	Midget Grooved (S5.7s)	T-1 3/4	0.63/16	0.24/6	1.1	30,000
02688	LED-14-BA9S-R	14 VAC/DC	Miniature Bayonet (BA9s)	T-3 1/4	1.0/25	0.40/10	0.75	30,000
02687	LED-14-BA9S-G	14 VAC/DC	Miniature Bayonet (BA9s)	T-3 1/4	1.0/25	0.40/10	1.5	30,000
02689	LED-14-BA9S-W	14 VAC/DC	Miniature Bayonet (BA9s)	T-3 1/4	1.0/25	0.40/10	2.4	30,000
02694	LED-24-BA9S-R	24~28 VAC/DC	Miniature Bayonet (BA9s)	T-3 1/4	1.0/25	0.40/10	0.7	30,000
02696	LED-24-BA9S-Y	24~28 VAC/DC	Miniature Bayonet (BA9s)	T-3 1/4	1.0/25	0.40/10	0.6	30,000
02693	LED-24-BA9S-G	24~28 VAC/DC	Miniature Bayonet (BA9s)	T-3 1/4	1.0/25	0.40/10	1.5	30,000
02695	LED-24-BA9S-W	24~28 VAC/DC	Miniature Bayonet (BA9s)	T-3 1/4	1.0/25	0.40/10	2.4	30,000
02679	LED-120-MB-R	110~130 VAC	Miniature Bayonet (BA9s)	T-3 1/4	1.0/25	0.40/10	0.2	30,000
02682	LED-120-MB-Y	110~130 VAC	Miniature Bayonet (BA9s)	T-3 1/4	1.0/25	0.40/10	0.2	30,000
02678	LED-120-MB-G	110~130 VAC	Miniature Bayonet (BA9s)	T-3 1/4	1.0/25	0.40/10	0.5	30,000
02681	LED-120-MB-W	110~130 VAC	Miniature Bayonet (BA9s)	T-3 1/4	1.0/25	0.40/10	0.6	30,000
02705	LED-24-PSB-R	24~28 VAC/DC	Slide Base 5 (TS5)	T-2	1.1/28	0.27/6.8	0.4	30,000
02706	LED-24-PSB-W	24~28 VAC/DC	Slide Base 5 (TS5)	T-2	1.1/28	0.27/6.8	1.1	30,000
02707	LED-24-PSB-Y	24~28 VAC/DC	Slide Base 5 (TS5)	T-2	1.1/28	0.27/6.8	0.4	30,000
02704	LED-24-PSB-G	24~28 VAC/DC	Slide Base 5 (TS5)	T-2	1.1/28	0.27/6.8	0.9	30,000
02684	LED-120-PSB-R	110~130 VAC	Slide Base 5 (TS5)	T-2	1.1/28	0.27/6.8	0.2	30,000
02686	LED-120-PSB-Y	110~130 VAC	Slide Base 5 (TS5)	T-2	1.1/28	0.27/6.8	0.2	30,000
02683	LED-120-PSB-G	110~130 VAC	Slide Base 5 (TS5)	T-2	1.1/28	0.27/6.8	0.6	30,000
02685	LED-120-PSB-W	110~130 VAC	Slide Base 5 (TS5)	T-2	1.1/28	0.27/6.8	0.9	30,000
02691	LED-14-T1.75 WEDGE-W	14 VAC/DC	Sub-Miniature Wedge (W2.1x4.6d)	T-1 3/4	0.77/19.4	0.22/5.5	1.1	30,000
02709	LED-24-T1.75 WEDGE-R*	24~28 VAC/DC	Sub-Miniature Wedge (W2.1x4.6d)	T-1 3/4	0.77/19.4	0.22/5.5	0.1	30,000
02711	LED-24-T1.75 WEDGE-W	24~28 VAC/DC	Sub-Miniature Wedge (W2.1x4.6d)	T-1 3/4	0.77/19.4	0.22/5.5	1.1	30,000
02712	LED-24-T1.75 WEDGE-Y*	24~28 VAC/DC	Sub-Miniature Wedge (W2.1x4.6d)	T-1 3/4	0.77/19.4	0.22/5.5	.3	30,000
05394	LED-12-SCBAY-W	12 VAC/DC	SC Bayonet (BA15s)	S-8	1.28/32.6	0.73/18.5	21.6	10,000
05379	LED-12-DCBAY-W	12 VAC/DC	DC Index Bayonet (BAY15d)	S-8	1.81/46	1.0/25	21.6/7.8	10,000

Continued on next page >>>

Miniature

Order Code	Item	Volts	Amps	Base	Bulb	Filament	MOL in/mm	MOD in/mm	Lumens	Life/Hrs
40672	385	28	0.04	Midget Flanged (SX6s)	T-1 3/4	C-2F	0.63/16.0	0.23/5.9	1.89	20,000
40674	386	14	0.08	Midget Grooved (S5.7s)	T-1 3/4	C-2F	0.63/16.0	0.23/5.9	3.77	40,000
40678	387	28	0.04	Midget Flanged (SX6s)	T-1 3/4	C-2F	0.63/16.0	0.23/5.9	3.77	10,000
40680	388	28	0.04	Midget Grooved (S5.7s)	T-1 3/4	C-2F	0.63/16.0	0.23/5.9	3.77	25,000
40686	394	12	0.04	Midget Flanged (SX6s)	T-1 3/4	C-2F	0.63/16.0	0.23/5.9	1.51	20,000
40692	399	28	0.04	Midget Screw (E5)	T-1 3/4	C-2F	0.72/18.3	0.23/5.9	3.77	7,000
40696	400	28	0.1	Miniature Wedge (W2.1x9.5d)	T-3 1/4	C-2F	1.06/26.9	0.40/10.2	20.11	1,000
40012	A3C	110	0.0018	Wire Leads (WL) (2" Leads)	T-2	Neon	0.75/19.1	0.25/6.4		25,000
40720	455	6.5	0.5	Miniature Bayonet (BA9s)	G-4 1/2	C-2R	1.07/27.2	0.59/15.0	23.88	500
40464	2114	6	0.06	Wire Leads (WL)	T-1 1/4	C-2R	0.46/11.7	0.17/4.3	1.63	3,000
41704	77A/S8	12	0.77	Single Contact Prefocus Flanged (P15s30)	S-8	C-8S	2.09/53.1	1.04/26.4	120	500
44326	56	5	0.115	Sub-Miniature Wedge (W2.1x4.9d)	T-1 3/4	C-2R	0.80/20.3	0.23/5.9	1.89	20,000
40468	2162	14	0.1	Wire Leads (WL)	T-1 3/4	C-2F	0.52/13.2	0.23/5.9	6.29	10,000
40470	2174	12	0.04	Wire Leads (WL)	T-1 3/4	C-2F	0.52/13.2	0.23/5.9	1.26	10,000
40472	2176	24	0.05	Wire Leads (WL)	T-1 3/4	C-2F	0.52/13.2	0.23/5.9	6.29	1,000
40478	2182	14	0.08	Wire Leads (WL)	T-1 3/4	C-2F	0.52/13.2	0.23/5.9	3.77	40,000
40484	2187	28	0.04	Wire Leads (WL)	T-1 3/4	C-2F	0.52/13.2	0.23/5.9	3.77	10,000
40488	2200	5	0.06	Wire Leads (WL)	T-1 3/4	C-2R	0.52/13.2	0.23/5.9	0.63	25,000
42384	2232	28	0.643	SC Bayonet (BA15s)	S-8	CC-8	2.00/50.8	1.04/26.4	225	2,000
42386	2233	28	0.766	SC Bayonet (BA15s)	S-8	CC-8	2.00/50.8	1.04/26.4	265	2,000
42231	2721	12	0.1	Sub-Miniature Wedge (W2x4.6d)	T-1 1/2	C-2V	0.80/20.3	0.20/5.1	6.03	1,000
40637	2825	13.5	0.4	Miniature Wedge (W2.1x9.5d)	T-3 1/4	C-2V	1.06/26.9	0.40/10.2	50	750
40114	PR7	3.7	0.3	SC Miniature Flanged (P13.5s)	B-3 1/2	C-2R	1.25/31.8	0.45/11.5	11.31	30
40084	PR12	5.95	0.5	SC Miniature Flanged (P13.5s)	B-3 1/2	C-2R	1.25/31.8	0.45/11.5	38	15
40086	PR13	4.75	0.5	SC Miniature Flanged (P13.5s)	B-3 1/2	C-2R	1.25/31.8	0.45/11.5	28	15
40090	PR15	4.82	0.5	SC Miniature Flanged (P13.5s)	B-3 1/2	C-2R	1.25/31.8	0.45/11.5	25	30
40092	PR16	12.5	0.25	SC Miniature Flanged (P13.5s)	B-3 1/2	C-2R	1.25/31.8	0.45/11.5	34	50
40096	PR18	7.2	0.55	SC Miniature Flanged (P13.5s)	B-3 1/2	C-2R	1.25/31.8	0.45/11.5	69	3
40102	PR20	8.63	0.5	SC Miniature Flanged (P13.5s)	B-3 1/2	C-2R	1.25/31.8	0.45/11.5	63	15
44011	P21/5W*	13.5/13.5	1.86/0.44	DC Index Bayonet (BAY15d)	S-8	C-6/C-6	2.06/52.5	1.05/26.5	440/35	300/2,000
50114	JF02XE	6	0.833	Rigid Loop (RGLP)	T-3 1/4	C-8	1.72/43.7	0.40/10.0	55	20,000
40106	PR30	3.75	0.86	SC Miniature Flanged (P13.5s)	B-3 1/2	C-2R	1.25/31.8	0.45/11.5	28	40
40446	2	5	0.021	Wire Leads (WL)	T-3/4	C-2R	0.20/5.1	0.09/2.3	0.38	10,000
50118	JF03XE*	12	0.417	Rigid Loop (RGLP)	T-3 1/4	C-8	1.72/43.7	0.40/10.0	60	3,000
40784	6S6/12V	12	0.5	Candelabra Screw (E12)	S-6	C-6	1.88/47.8	0.75/19.1	48	1,500
40792	6S6/24V	24	0.25	Candelabra Screw (E12)	S-6	C-6	1.88/47.8	0.75/19.1	53	1,500
40794	6S6/30V	30	0.2	Candelabra Screw (E12)	S-6	C-6	1.88/47.8	0.75/19.1	52	1,500
40796	6S6/48V	48	0.125	Candelabra Screw (E12)	S-6	C-6	1.88/47.8	0.75/19.1	47	1,500
40800	6S6/60V	60	0.1	Candelabra Screw (E12)	S-6	C-7A	1.88/47.8	0.75/19.1	43	1,500
40786	6S6/120V	120	0.05	Candelabra Screw (E12)	S-6	C-7A	1.88/47.8	0.75/19.1	39	1,500
40790	6S6/155V	155	0.039	Candelabra Screw (E12)	S-6	C-7A	1.88/47.8	0.75/19.1	33	1,500
40791	6S6/230V	230	0.026	Candelabra Screw (E12)	S-6	C-7A	1.88/47.8	0.75/19.1	11.31	1,500
43004	15T7N-130V	130	0.12	Intermediate Screw (E17)	T-7	C-7A	2.25/57.2	0.89/22.6	90	1,500
40218	12ESB5*	12	0.04	Slide Base 5 (TS5)	T-2	C-2V	0.92/23.4	0.27/6.9		7,500
40220	12MB	12	0.17	Miniature Bayonet (BA9s)	T-2 1/2	C-2F	1.19/30.2	0.33/8.4	4.40	12,000
40222	12PSB5	12	0.17	Slide Base 5 (TS5)	T-2	C-2F	1.11/28.2	0.27/6.9		12,000

Continued on next page >>>