



Miniature Lamps

EIKO offers one of the widest lines of miniature lamps in the industry. Featuring quality construction with durable design, our lamps meet or exceed SAE and/or ANSI specifications for lumen output and lifetime hours and are known for their long-term reliability. Our in-house testing facilities ensure product quality. Available in traditional incandescent lamps or energy-efficient LED lamps that feature extraordinary long life.

LED Miniature Lamps

Order Code	Item	Volts	Base	Bulb	MOL in/ mm	MOD in/ mm	Lumens	Life/Hrs
02697	LED-24-MF-R*	24~28 VAC/DC	Midget Flanged (SX6s)	T-1 3/4	0.63/16	0.24/6	0.7	30,000
02698	LED-24-MF-W	24~28 VAC/DC	Midget Flanged (SX6s)	T-1 3/4	0.63/16	0.24/6	3.2	30,000
02702	LED-24-MG-W	24~28 VAC/DC	Midget Grooved (S5.7s)	T-1 3/4	0.63/16	0.24/6	1.1	30,000
02688	LED-14-BA9S-R	14 VAC/DC	Miniature Bayonet (BA9s)	T-3 1/4	1.0/25	0.40/10	0.75	30,000
02687	LED-14-BA9S-G	14 VAC/DC	Miniature Bayonet (BA9s)	T-3 1/4	1.0/25	0.40/10	1.5	30,000
02689	LED-14-BA9S-W	14 VAC/DC	Miniature Bayonet (BA9s)	T-3 1/4	1.0/25	0.40/10	2.4	30,000
02694	LED-24-BA9S-R	24~28 VAC/DC	Miniature Bayonet (BA9s)	T-3 1/4	1.0/25	0.40/10	0.7	30,000
02696	LED-24-BA9S-Y	24~28 VAC/DC	Miniature Bayonet (BA9s)	T-3 1/4	1.0/25	0.40/10	0.6	30,000
02693	LED-24-BA9S-G	24~28 VAC/DC	Miniature Bayonet (BA9s)	T-3 1/4	1.0/25	0.40/10	1.5	30,000
02695	LED-24-BA9S-W	24~28 VAC/DC	Miniature Bayonet (BA9s)	T-3 1/4	1.0/25	0.40/10	2.4	30,000
02679	LED-120-MB-R	110~130 VAC	Miniature Bayonet (BA9s)	T-3 1/4	1.0/25	0.40/10	0.2	30,000
02682	LED-120-MB-Y	110~130 VAC	Miniature Bayonet (BA9s)	T-3 1/4	1.0/25	0.40/10	0.2	30,000
02678	LED-120-MB-G	110~130 VAC	Miniature Bayonet (BA9s)	T-3 1/4	1.0/25	0.40/10	0.5	30,000
02681	LED-120-MB-W	110~130 VAC	Miniature Bayonet (BA9s)	T-3 1/4	1.0/25	0.40/10	0.6	30,000
02705	LED-24-PSB-R	24~28 VAC/DC	Slide Base 5 (TS5)	T-2	1.1/28	0.27/6.8	0.4	30,000
02706	LED-24-PSB-W	24~28 VAC/DC	Slide Base 5 (TS5)	T-2	1.1/28	0.27/6.8	1.1	30,000
02707	LED-24-PSB-Y	24~28 VAC/DC	Slide Base 5 (TS5)	T-2	1.1/28	0.27/6.8	0.4	30,000
02704	LED-24-PSB-G	24~28 VAC/DC	Slide Base 5 (TS5)	T-2	1.1/28	0.27/6.8	0.9	30,000
02684	LED-120-PSB-R	110~130 VAC	Slide Base 5 (TS5)	T-2	1.1/28	0.27/6.8	0.2	30,000
02686	LED-120-PSB-Y	110~130 VAC	Slide Base 5 (TS5)	T-2	1.1/28	0.27/6.8	0.2	30,000
02683	LED-120-PSB-G	110~130 VAC	Slide Base 5 (TS5)	T-2	1.1/28	0.27/6.8	0.6	30,000
02685	LED-120-PSB-W	110~130 VAC	Slide Base 5 (TS5)	T-2	1.1/28	0.27/6.8	0.9	30,000
02691	LED-14-T1.75 WEDGE-W	14 VAC/DC	Sub-Miniature Wedge (W2.1x4.6d)	T-1 3/4	0.77/19.4	0.22/5.5	1.1	30,000
02709	LED-24-T1.75 WEDGE-R*	24~28 VAC/DC	Sub-Miniature Wedge (W2.1x4.6d)	T-1 3/4	0.77/19.4	0.22/5.5	0.1	30,000
02711	LED-24-T1.75 WEDGE-W	24~28 VAC/DC	Sub-Miniature Wedge (W2.1x4.6d)	T-1 3/4	0.77/19.4	0.22/5.5	1.1	30,000
02712	LED-24-T1.75 WEDGE-Y*	24~28 VAC/DC	Sub-Miniature Wedge (W2.1x4.6d)	T-1 3/4	0.77/19.4	0.22/5.5	.3	30,000
05394	LED-12-SCBAY-W	12 VAC/DC	SC Bayonet (BA15s)	S-8	1.28/32.6	0.73/18.5	21.6	10,000
05379	LED-12-DCBAY-W	12 VAC/DC	DC Index Bayonet (BAY15d)	S-8	1.81/46	1.0/25	21.6/7.8	10,000

Continued on next page >>>

Order Code	Item	Volts	Amps	Base	Bulb	Filament	MOL in/ mm	MOD in/ mm	Lumens	Life/Hrs
43000	15T6C-130V	130	0.12	Candelabra Screw (E12)	T-6	C-7A	3.06/77.7	0.77/19.6	90	2,000
43002	15T6C-145V	145	0.1	Candelabra Screw (E12)	T-6	C-7A	3.06/77.7	0.77/19.6	90	2,000 (7,500 @ 120V)
40291	16ESB5	16	0.04	Slide Base 5 (TS5)	T-2	C-2F	0.92/23.4	0.27/6.9		7,500
44322	17	28	0.065	Sub-Miniature Wedge (W2.1x4.9d)	T-1 3/4	C-2F	0.80/20.3	0.23/5.9	8.17	5,000
43014	20T6-1/2DC-130V	130	0.15	DC Bayonet (BA15d)	T-6 1/2	C-8	5.56/141.2	0.83/21.1	180	3,000
41002	8918	14	0.1	Midget Flanged (SX6s)	T-1 3/4	C-2F	0.63/16.0	0.23/5.9	6.29	10,000
42005	42005	135 V	0.32	Bi-Pin .050 (G127)	T-1	C-2R	0.38/9.7	0.13/3.2	2.14	5
42003	42003	2.7	0.32	Bi-Pin .050 (G127)	T-1	C-2R	0.38/9.7	0.13/3.2	8.80	5
42006	42006	2.7	0.32	Bi-Pin .050 (G127)	T-1	C-2R	0.38/9.7	0.13/3.2	8.80	5
40010	A2B	110	0.0007	Wire Leads (WL) (2" Leads)	T-2	Neon	0.75/19.1	0.25/6.4		25,000
40814	6S6DC/6V	6	1.0	DC Bayonet (BA15d)	S-6	C-6	1.82/46.2	0.75/19.1	54	1,500
40986	87	6.8	1.91	SC Bayonet (BA15s)	S-8	C-6	2.00/50.8	1.04/26.4	190	300
43036	25T10/F-130V	130	0.19	Medium Screw (E26)	T-10	C-8	5.19/131.8	1.25/31.8	200	1,500
50124	JF07XE	12	0.833	Rigid Loop (RGLP)	T-3 1/4	C-8	1.72/43.7	0.40/10.0	100	20,000
43022	25T6.5N/F-130V	130	0.19	Intermediate Screw (E17)	T-6 1/2	C-8	5.5/139.7	0.83/21.1	200	3,000
43020	25T6-1/2N-130V	130	0.19	Intermediate Screw (E17)	T-6 1/2	C-8	5.5/139.7	0.83/21.1	210	3,000
50132	JF13XE*	24	0.208	Rigid Loop (RGLP)	T-3 1/4	C-8	1.72/43.7	0.40/10.0	55	3,000
05833	6614F	14	0.05	Double End Cap (SF6/6)	T-2	C-8	1.26/32.0	0.24/6.1	2.01	10,000
40841	6612F	12	0.25	Double End Cap (SF6/6)	T-2	C-8	1.26/32.0	0.24/6.1	12.57	5,000
42382	1662	28/28	0.93/0.34	DC Index Bayonet (BAY15d)	S-8	CC-6/C-6	2.00/50.8	1.04/26.4	400/75	400/1,000
44402	20T6-1/2N-145V	145	0.14	Intermediate Screw (E17)	T-6 1/2	C-8	5.5/139.7	0.83/21.1	170	3,000
40000	A1A	110	0.0006	Wire Leads (WL) (1.25" Leads)	T-2	Neon	1.00/25.4	0.25/6.4		25,000
44021	795X	12.8	3.91	SC Bayonet (BA15s)	T-4	C-8	2.50/63.5	0.48/12.2	1355	200
40492	222	2.25 V	0.25	Miniature Screw (E10)	TL-3	C-2R	0.93/23.6	0.38/9.6		5
40520	243	2.33 V	0.27	Miniature Screw (E10)	TL-3	C-6	0.93/23.6	0.38/9.6		10
40534	259	6.3	0.25	Miniature Wedge (W2.1x9.5d)	T-3 1/4	C-2R	1.06/26.9	0.40/10.2	8.17	5,000
40550	293	14	0.33	Miniature Bayonet (BA9s)	G-4 1/2	C-2F	1.07/27.2	0.59/15.0	25	5,000
40562	303	28	0.3	SC Bayonet (BA15s)	G-6	CC-6	1.44/36.6	0.75/19.1	75	500
40566	306	28	0.51	DC Bayonet (BA15d)	S-8	C-6	2.00/50.8	1.04/26.4	190	300
40568	307	28	0.67	SC Bayonet (BA15s)	S-8	C-6	2.00/50.8	1.04/26.4	265	300
40570	308	28	0.67	DC Bayonet (BA15d)	S-8	C-6	2.00/50.8	1.04/26.4	265	300
40576	311	28	1.29	SC Bayonet (BA15s)	S-11	CC-2V	2.38/60.5	1.35/34.3	630	300
40728	464	28	0.17	Miniature Wedge (W2.1x9.5d)	T-3 1/4	C-2F	1.06/26.9	0.40/10.2	38	1,500
40752	503	5.1	0.15	Miniature Bayonet (BA9s)	G-4 1/2	C-2R	1.07/27.2	0.59/15.0	7.54	100
40225	120MB-NEON	120	0.004	Miniature Bayonet (BA9s)	T-3	Neon	1.19/30.2	0.38/9.6		10,000
40754	509K	24	0.18	Candelabra Screw (E12)	G-6	C-2F	1.38/35.1	0.75/19.1	35	1,000
40783	555	6.3	0.25	Miniature Wedge (W2.1x9.5d)	T-3 1/4	C-2R	1.06/26.9	0.40/10.2	11.31	3,000
40769	558	13	0.33	Miniature Wedge (W2.1x9.5d)	T-3 1/4	C-2V	1.06/26.9	0.40/10.2		500
40759	585	28	0.04	Miniature Wedge (W2.1x9.5d)	T-3 1/4	C-2F	1.06/26.9	0.40/10.2	3.77	7,000
40828	623	28	0.37	SC Bayonet (BA15s)	G-6	2C-6	1.44/36.6	0.75/19.1	75	1,000
40165	1073	12.8	1.8	SC Bayonet (BA15s)	S-8	C-6	2.00/50.8	1.04/26.4	400	200
40167	1076	12.8	1.8	DC Bayonet (BA15d)	S-8	C-6	2.00/50.8	1.04/26.4	400	200
40172	1130	6.4	2.63	DC Bayonet (BA15d)	S-8	C-6	2.00/50.8	1.04/26.4	265	200
40176	1141	12.8	1.6	SC Bayonet (BA15s)	S-8	C-6	2.00/50.8	1.04/26.4	265	1,500
40178	1142	12.8	1.6	DC Bayonet (BA15d)	S-8	C-6	2.00/50.8	1.04/26.4	265	1,000
40244	1252	28	0.23	DC Bayonet (BA15d)	G-6	C-6/C-6	1.44/36.6	0.75/19.1	38	2,000
40250	1309	28	0.52	SC Bayonet (BA15s)	B-6	2C-6	1.75/44.5	0.79/20.1	190	300
40258	1383	13	1.5	SC Bayonet (BA15s)	R-12	C-8	2.63/66.8	1.55/39.4	200	300
40262	1385	28	0.72	SC Bayonet (BA15s)	R-12	CC-8	2.63/66.8	1.55/39.4	165	300
49013	1236X	12	0.3	Miniature Wedge (W2.1x9.5d)	T-3 1/4	C-2V	1.06/26.9	0.40/10.2	45	20,000
49015	1210X	12	0.833	Miniature Wedge (W2.1x9.5d)	T-3 1/4	C-2V	1.06/26.9	0.40/10.2	125	2,000

Continued on next page >>>