

UTILITY LIGHTING


CEILING MOUNT LUMAIRES

- UL Listed. File Number: E182610. Suitable for use in damp locations ONLY!
- Meets the requirements of the 2017 National Electrical Code: Articles 314.16(A)(2), 314.17(C), 410.10(A) and 547.5(C)(1) and (2).
- Includes porcelain E26 lamp socket with corrosion resistant nickel-plated brass screw shell.
- High impact, corrosion resistant, compression molded phenolic junction box and luminaire base.
- Standard and Tempered Glass Globes rated for "A" Series incandescent lamps (150-watt maximum).
- Polycarbonate and Acrylic Prismatic Globes rated for "A" Series incandescent lamps (60-watt maximum).
- All ceiling mount luminaires are supplied with a neoprene gasket, corrosion resistant screws and rubber washer. Wired with 194°F (90°C) minimum supply wires (THHN).



TYPICAL APPLICATIONS:

- Walk-in Refrigerators
- Elevator Shafts
- Tunnels
- Storage Buildings
- Maintenance Areas
- Swine and Poultry Confinement Buildings



Catalog Number	UPC Number	Description	Order Unit	Unit Qty	Unit Pkg	Units/Case	TL Case Qty	Min Order Qty	MM Req	Ship Wt (Lbs)
With 12 Cubic Inch Junction Box (15045)										
15000	15000	Utility Luminaire: 1/2" and 3/4" Knockout Combo - Standard Glass Globe	EA	1	BX	12	12	12	Yes	24
15001	15001	Utility Luminaire: 1/2" and 3/4" Knockout Combo - Tempered Glass Globe	EA	1	BX	12	12	12	Yes	24
15002	15002	Utility Luminaire: 3/4" Knockout - Standard Glass Globe	EA	1	BX	12	12	12	Yes	24
15005	15005	Utility Luminaire: 1/2" and 3/4" Knockout Combo - Polycarbonate Globe	EA	1	BX	12	12	1	No	18
15006	15006	Utility Luminaire: 1/2" and 3/4" Knockout Combo - Acrylic Prismatic Globe (Tall)	EA	1	BX	12	12	1	No	19
15007	15007	Utility Luminaire: 1/2" and 3/4" Knockout Combo - Acrylic Prismatic Globe	EA	1	BX	12	12	1	No	19
Without Junction Box										
15050	15050	Utility Luminaire: Standard Glass Globe	EA	1	BX	12	12	12	Yes	20
15051	15051	Utility Luminaire: Tempered Glass Globe	EA	1	BX	12	12	12	Yes	20
15055	15055	Utility Luminaire: Polycarbonate Clear Globe	EA	1	BX	12	12	1	No	14
15056	15056	Utility Luminaire: Acrylic Prismatic Globe (Tall)	EA	1	BX	12	12	1	No	15
15090	15090	Medium Bases: Globe not included	EA	1	BX	12	12	1	No	7

UNITS OF MEASURE KEY

Order Unit: The Unit to be ordered; Order Qty: Number of pieces in each Unit; Unit Pkg: Packaging types - BG (Bag), BX (Box), BN (Bulk); Units/Case: Unit packages contained in the Case; TL Case Qty: The total number of items in each Master Case; Min Order Qty: The smallest Unit that can be ordered; MM Req: Must order multiples of the Unit in the stated quantities; Ship Wt (Lbs): Total weight of the units per Carton

Specifications subject to change without prior notice.

UTILITY LIGHTING

STANDARD NON-METALLIC JUNCTION BOXES

- UL Listed. File Number: E182992.
- High impact, compression molded phenolic plastic rated to 302°F (150°C).
- Meets the requirements of the 2017 National Electrical Code: Articles 314.15, 314.16(A)(2), 314.17(C), and 547.5(C)(1) and (2).
- Suitable for use in "wet" locations.
- Corrosion resistant.



Catalog Number	UPC Number	Description	Order Unit	Unit Qty	Unit Pkg	Units/ Case	TL Case Qty	Min Order Qty	MM Req	Ship Wt (Lbs)
15045	15045	12 Cubic Inch Junction Box: 1/2" and 3/4" Knockout Combo	EA	1	BX	12	12	12	Yes	6
15046	15046	12 Cubic Inch Junction Box: 1/2" Knockouts	EA	1	BX	12	12	12	Yes	6
15047	15047	12 Cubic Inch Junction Box: 3/4" Knockouts	EA	1	BX	12	12	12	Yes	6
15049	15049	19 Cubic Inch Junction Box: 3/4" Knockouts	EA	1	BX	12	12	12	Yes	6
15070	15070	16 Cubic Inch Single-Gang FS-C Type Junction Box: 1/2" Knockouts	EA	1	BX	12	12	12	Yes	6
15071	15071	16 Cubic Inch Single-Gang FS-C Type Junction Box: 3/4" Knockouts	EA	1	BX	12	12	12	Yes	6
15075	15075	Single-Gang Junction Box Cover and Neoprene Gasket	EA	1	BX	12	12	12	Yes	2
15905	15905	Round Junction Box Cover and Neoprene Gasket	EA	1	BX	12	12	12	Yes	2

SPIDERBOX™ NON-METALLIC JUNCTION BOXES

- UL Listed. File Number: E182992.
- Suitable for use in "wet" locations.
- Corrosion resistant.
- Easy to install using the eight (8) mounting brackets that are in-line with knockouts.
- Eliminates a 2" x 4" stub-in.
- High impact compression molded phenolic plastic rated to 302°F (150°C).
- Meets the requirements of the 2017 National Electrical Code: Articles 314.15, 314.16(A)(2), 314.17(C), 547.5(C)(1) and (2).



COMPACT FLUORESCENT LAMPS

T3 Coil
23-Watt Spiral
Compact
Fluorescent
Lamp
(P/N: 15680)



Catalog Number	UPC Number	Description	Order Unit	Unit Qty	Unit Pkg	Units/ Case	TL Case Qty	Min Order Qty	MM Req	Ship Wt (Lbs)
SPIDERBOX Non-Metallic Junction Boxes										
15246	15246	12 Cubic Inch SPIDERBOX Junction Box: 1/2" Knockouts	EA	1	BX	12	12	12	Yes	6
15247	15247	12 Cubic Inch SPIDERBOX Junction Box: 3/4" Knockouts	EA	1	BX	12	12	12	Yes	6
15905	15905	Round Junction Box Cover and Silicone Gasket	EA	1	BX	12	12	12	Yes	2
Compact Fluorescent Lamp										
15680	15680	Compact Fluorescent Lamp: 23-watt, Self-Ballasted Lamp (5000K); Lumen output is equal to a 100-watt Incandescent Lamp	EA	1	BX	50	50	1	No	8

UNITS OF MEASURE KEY

Order Unit: The Unit to be ordered; Order Qty: Number of pieces in each Unit; Unit Pkg: Packaging types - BG (Bag), BX (Box), BN (Bulk); Units/Case: Unit packages contained in the Case; TL Case Qty: The total number of items in each Master Case; Min Order Qty: The smallest Unit that can be ordered; MM Req: Must order multiples of the Unit in the stated quantities; Ship Wt (Lbs): Total weight of the units per Carton

Specifications subject to change without prior notice.

LUMINAIRE GLOBES


STANDARD AND TEMPERED GLASS GLOBES

- Withstands extreme temperature changes.
- For use with "A" Series incandescent lamps (150-watt maximum).

ACRYLIC PRISMATIC and POLYCARBONATE GLOBES

- UV stabilized material. The Acrylic Prismatic Globes resist discoloration four times longer than polycarbonate material.
- 3 Year guarantee against discoloration from UV exposure. For applications that require high-pressure wash down.
- Acrylic Prismatic Globes feature internal ribbing and smooth exterior.
- For use with "A" Series incandescent lamps (60-watt maximum).

- (a) Acrylic Prismatic Globe (Tall)
 (b) Standard Glass Globe
 (c) Tempered Glass Globe
 (d) Polycarbonate Clear Globe



Catalog Number	UPC Number	Description	Order Unit	Unit Qty	Unit Pkg	Units/ Case	TL Case Qty	Min Order Qty	MM Req	Ship Wt (Lbs)
15015	15015	Standard Glass Globe	EA	1	BX	32	32	32	Yes	34
15016	15016	Tempered Glass Globe	EA	1	BX	32	32	32	Yes	34
15020	15020	Polycarbonate Clear Globe	EA	1	BX	12	12	12	No	5
15025	15025	Acrylic Prismatic Globe (Tall)	EA	1	BX	12	12	12	No	5

Note: Luminaire Globes are sold ONLY in case quantities.

REPLACEMENT LAMP SOCKET

- High temperature porcelain lamp socket with 6-inch 18 AWG stranded wire leads.
- Includes corrosion resistant nickel-plated brass screw shell.
- Can be used with "A" Series incandescent lamps (150-watt maximum).



Catalog Number	UPC Number	Description	Order Unit	Unit Qty	Unit Pkg	Units/ Case	TL Case Qty	Min Order Qty	MM Req	Ship Wt (Lbs)
15031	15031	Replacement Lamp Socket: Porcelain	BG	12	BG	0	0	12	Yes	1

Note: Porcelain lamp sockets are interchangeable with luminaires built with phenolic sockets.

WIRE GUARD

- Fits Standard Glass, Tempered Glass and Acrylic Prismatic (short) Globes only.
- 8 AWG steel, with a three-coat electrolytic plating.
- Clamp-type attachment.



Catalog Number	UPC Number	Description	Order Unit	Unit Qty	Unit Pkg	Units/ Case	TL Case Qty	Min Order Qty	MM Req	Ship Wt (Lbs)
15063	15063	Wire Guard	EA	1	BX	0	0	1	No	2

UNITS OF MEASURE KEY

Order Unit: The Unit to be ordered; Order Qty: Number of pieces in each Unit; Unit Pkg: Packaging types - BG (Bag), BX (Box), BN (Bulk); Units/Case: Unit packages contained in the Case; TL Case Qty: The total number of items in each Master Case; Min Order Qty: The smallest Unit that can be ordered; MM Req: Must order multiples of the Unit in the stated quantities; Ship Wt (Lbs): Total weight of the units per Carton

Specifications subject to change without prior notice.

Distributed by:

Specifications subject to change without prior notice.

E02-019-000 B1 (7/17-SP)
©2017 Engineered Products Company. All Rights Reserved.
SpiderBox is a trademark of Engineered Products Company.