






# nVent CADDY Speed Link SLK with Y-Hook – SLK2YH500L2



- Complete system includes wire, locking device and two pre-assembled hook end fittings
- Fastens to the building structure and hooks to hanging services and tray
- Spring latch helps provide secure connection
- Convenient design allows one hook to be temporarily detached for maintenance or to add cables to the tray
- Single drop with double hook provides increased stability to the system
- Also available in a single-hook end fitting configuration



|                           |                                      |
|---------------------------|--------------------------------------|
| Part Number               | SLK2YH500L2                          |
| Material                  | Steel<br>Zinc Alloy<br>Polypropylene |
| Finish                    | Electrogalvanized                    |
| Static Load Safety Factor | 5:1                                  |
| Complies With             | SMACNA HVAC-DCS                      |
| Wire Rope Diameter        | 2 mm                                 |
| Wire Rope Length          | 6.6'                                 |
| Wire Rope "Y" Length (YL) | 19.6"                                |
| A                         | 2.3"                                 |
| B                         | 0.9"                                 |
| C                         | 1/4"                                 |
| Static Load (F)           | 100 lb                               |
| Height (H)                | 2.15"                                |
| Width (W)                 | 3/4"                                 |
| Thickness (T)             | 1/2"                                 |
| Angle (a)                 | 90° Max                              |
| Certifications            | cULus                                |

|                             |               |
|-----------------------------|---------------|
| Part Number                 | SLK2YH500L2   |
| Standard Packaging Quantity | 10 pc         |
| UPC                         | 78285680173   |
| EAN-13                      | 8711893137880 |

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

#### WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.erico.com](http://www.erico.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2019 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.

