





SNSW Flanged Nut – SNSW50



- Ideal for retrofit projects, such as trapeze installations, where disassembly of the support system is not desired
- Use as a stopper when installing nVent CADDY Rod Lock assemblies
- Can be easily installed, removed, and repositioned at any location along the threaded rod
- Ready to use out of the box and eliminates multiple pieces of standard hardware
- Functions as a hex nut and flat washer combined
- Washer is wide enough to work with standard strut channel profiles



Part Number	SNSW50
Material	Steel
Finish	Electrogalvanized
Static Load Safety Factor	3:1
Rod Size (RS)	1/2"
Diameter (Ø)	1.9"
A	0.95"
B	1/4"
Wrench Size	1"
Static Load (F)	300 lb
Standard Packaging Quantity	20 pc
UPC	78285686172

For use on plain and electro zinc plated hardware only.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2019 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.

