


# CADDY® ROD LOCK Anchor Screw




| Part Number | Article Number | Rod Size | Material                                          | Drill Bit Size | Drill Hole Depth | Ultimate Pullout | Allowable Pullout | Socket Size |
|-------------|----------------|----------|---------------------------------------------------|----------------|------------------|------------------|-------------------|-------------|
| CRLA37EG    | N/A            | 3/8"     | 3,000 psi<br>[20.68 Mpa]<br>or higher<br>concrete | 5/16"          | 2"               | 2,000 lbs        | 667 lbs           | 7/8"        |
| CRLAM8EG    | 390009         | M8       |                                                   | 8mm            | 50mm             | 8,800N           | 2,933 N           | 22mm        |
| CRLAM10EG   | 390010         | M10      |                                                   | 8mm            | 50mm             | 8,800N           | 2,933 N           | 22mm        |
| CRLA37EG    | N/A            | 3/8"     | Soft Wood                                         | 9/32"          | 2"               | 2,000 lbs        | 667 lbs           | 7/8"        |
|             |                |          | Hard Wood                                         | 9/32"          |                  | 2,000 lbs        | 667 lbs           |             |
|             |                |          |                                                   | 5/16"          |                  | 1,750 lbs        | 583 lbs           |             |

Not for use with hot dip galvanized hardware/components


## FM® Approved only on Concrete

| Part Number | Article Number | Rod Size | FM Load   | FM Maximum Pipe Size |
|-------------|----------------|----------|-----------|----------------------|
| CRLA37EG    | N/A            | 3/8"     | 1,475 lbs | 4"                   |
| CRLAM10EG   | 390010         | M10      | 6,550N    | DN100                |



| Kit Part Number | Description                                                 |
|-----------------|-------------------------------------------------------------|
| CRLAKITA        | 22mm CADDY ROD LOCK Drive Socket Kit (purchased separately) |



**CRLAKITA**



Load



### WARNING:

1. ERICO products shall be installed and used only as indicated in ERICO product instruction sheets and training materials. Instruction sheets are available at [www.erico.com](http://www.erico.com) and from your ERICO customer service representative.
2. ERICO products must never be used for a purpose other than the purpose for which they were designed or in a manner that exceeds specified load ratings.
3. All instructions must be completely followed to ensure proper and safe installation and performance.
4. Improper installation, misuse, misapplication or other failure to completely follow ERICO's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death.
5. Products that are manufactured using spring steel components shall be used only in a non-corrosive indoor environment.
6. All pipe supports, hangers, intermediate components and structural attachments must ONLY be used as described herein and are NEVER to be used for any other purpose.

NOTE: All load ratings are for static conditions and do not account for dynamic loading such as wind, water or seismic loads, unless otherwise noted.

The customer is responsible for:

- a. Conformance to all governing codes.
- b. The integrity of structures to which the products are attached, including their capability of safely accepting the loads imposed, as evaluated by a qualified engineer.
- c. Using appropriate industry standard hardware as noted above.

### SAFETY INSTRUCTIONS:

All governing codes and regulations and those required by the job site must be observed. Always use appropriate safety equipment such as eye protection, hard hat, and gloves as appropriate to the application.

CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH, and LENTON are registered trademarks of ERICO International Corporation.

FM is a registered certification mark of FM Approvals LLC, LTD

TECHNICAL SUPPORT:  
[www.erico.com](http://www.erico.com)


CFS414\_E

1 OF 2 © 2009, 2010, 2014, 2015 ERICO International Corporation


**ERICO®**




# CADDY® ROD LOCK Anchor Screw



Use the right drill bit size per Table.





Drill hole depth - 2" or 50 mm per Table.  
Suggested drill speed: 1000-1300 rpm




Use CRLAKITA kit (Purchased Separately) or  
use a 7/8" or 22 mm socket per Table.

CADDY® ROD LOCK  
Anchor Screw



Suggested speed: 1000-1300 rpm.



Push in threaded rod.  
Optional to fully  
tighten threaded rod.

