

Catalog numbers:

Catalog no.	Optional covers*	Fuse amp range	Lineside (conductors per port)					Loadside (conductors per port)									
			Poles	Conductors	Ports/ pole	Torque AWG	N-m (lb-in)	Conductors	Ports/ pole	Torque AWG	N-m (lb-in)						
JM60030-1MW14	N/A	up to 30	1	Cu 2-14 Al 2-8	1	2-3	5.6 (50)	Cu (1) 8-14 Cu (2) 12-14*** Al (1) 8 Str Al (1) 10 Sol	4	Cu (1) 8	3.4 (30)						
JM60030-2MW14			4-6			5.1 (45)	Cu (1) 10-14			2.8 (25)							
JM60030-3MW14			8			4.5 (40)	Cu (2) 12-14			3.4 (30)							
			10-14			4.0 (35)	Al (1) 8-10			3.4 (30)							
JM60060-1MW12†	CVR-J-60060 CVRI-J-60060**	35 - 60	1	Cu 2-14 Al 2-8	2	2-4	5.6 (50)	Cu 2-14 Al 2-8	1	2-3	5.6 (50)						
JM60060-2MW12†			6-10			4.5 (40)	4-6			5.1 (45)							
JM60060-3MW12†			12-14			1.7 (15)	8			4.5 (40)							
							10-14			4.0 (35)							
JM60060-1MW14†			1			2-3	5.6 (50)			Cu (1) 8-14 Cu (2) 12-14*** Al (1) 8 Str Al (1) 10 Sol	4	Cu (1) 8	3.4 (30)				
JM60060-2MW14†			2			4-6	5.1 (45)					Cu (1) 10-14	2.8 (25)				
JM60060-3MW14†			3			8	4.5 (40)					Cu (2) 12-14	3.4 (30)				
						10-14	4.0 (35)					Al (1) 8-10	3.4 (30)				
JM60060-1MW24						1	2-4			5.6 (50)	Cu (1) 8-14 Cu (2) 12-14*** Al (1) 8 Str Al (1) 10 Sol	4	Cu (1) 8	3.4 (30)			
JM60060-2MW24			2			6-10	4.5 (40)			Cu (1) 10-14			2.8 (25)				
JM60060-3MW24			3			12-14	1.7 (15)			Cu (2) 12-14			3.4 (30)				
										Al (1) 8-10			3.4 (30)				
JM60100-1MW14	CVR-J-60100-M CVRI-J-60100-M**	70 - 100	1	Cu 1/0-14 Al 1/0-12	1	1/0-3; Cu (2) 4-6	5.6 (50)	Cu (1) 4-14 Al (1) 4-8 Cu (2) 10-14***	4	4-6	4.0 (35)						
JM60100-2MW14			4-6; Cu (2) 8			5.0 (45)	8			2.8 (25)							
JM60100-3MW14			8; Cu (2) 10-14			4.5 (40)	Cu 10-14			2.3 (20)							
			10-14			4.0 (35)	(2) 10-14			3.4 (30)							
JM60200-1MW16	CVR-J-60200-M CVRI-J-60200-M**	110-200	1	Cu/Al (1) 250kcmil-6 Cu (2) 2-6	1	250kcmil-1	42 (375)	Cu (1) 4-14 Al (1) 4-8 Cu (2) 10-14***	6	4-6	4.0 (35)						
JM60200-2MW16							8			2.8 (25)							
JM60200-3MW16			2-6			31 (275)	10-14			2.3 (20)							
										(2) 10-14	3.4 (30)						
JM60400-1MW16	CVR-J-60400-M CVRI-J-60400-M**	225-400	1	Cu/Al (1) 600kcmil-4 Cu/Al (2) 3/0-4	1	600kcmil	57 (500)	Cu (1) 2-14 Al (1) 2-8 Cu (2) 8-14***	6	2-3	5.6 (50)						
JM60400-2MW16			2							4-6	5.0 (45)						
							500kcmil-4			51 (450)	8	4.5 (40)					
JM60400-3MW16											(2) 8	4.5 (40)					
			3			Cu (2) 3/0-4 Al (2) (3/0-4	57 (500) 34 (300)			10-14	4.0 (35)						
													(2) 10-14	4.5 (40)			
JM60400-1MW26						1							2-3	5.6 (50)			
JM60400-2MW26						2							4-6	5.0 (45)			
JM60400-3MW26												350kcmil-1	42 (375)	Cu (1) 2-14 Al (1) 2-8 Cu (2) 8-14***	6	8	4.5 (40)
														10-14	4.0 (35)		
						2-6	31 (275)	(2) 10-14	4.5 (40)								

* Order one cover per pole.

** With open fuse indication. 90 V minimum and closed circuit required for illumination.

*** Dual wire rated lugs with same wire size and stranding.

† Rated for 75°C Cu/Al conductors. Conductors with higher ratings may be used with appropriate derating.