Rigid Conduit and IMC Locknuts

NEC/CEC:
Listed for Ordinary Locations

Application

- Used to secure and ground conduits and fittings to enclosures.

Material

- Zinc plated steel or aluminum

NEC/CEC Certifications and Compliances

- UL Standard: 514B
- UL Listed: E-11853, E-24264
- CSA Standard: C22.2 No. 18.3
- CSA Certified: 065178
- NEMA: FB-1

	Trade Size (Inches)	Dimensions in Millimeters (Inches) Diameter	Height	Weight per 100 kg (lb)	Appleton™ Catalog Number	O–Z/Gedney™ Catalog Number
Locknuts — Steel						
	3/8	23.9 (0.94)	3.3 (0.13)	0.64 (1.40)	**BL38**	**1–38S**
	1/2	28.7 (1.13)	3.3 (0.13)	0.59 (1.30)	**BL50**	**1–50S**
	3/4	35.1 (1.38)	3.3 (0.13)	1.09 (2.40)	**BL75**	**1–75S**
	1	42.9 (1.69)	4.8 (0.19)	1.81 (4.00)	**BL100**	**1–100S**
	1-1/4	57.2 (2.25)	4.8 (0.19)	2.49 (5.50)	**BL125**	**1–125S**
	1-1/2	60.5 (2.38)	4.8 (0.19)	4.54 (10.00)	**BL150**	**1–150S**
	2	73.2 (2.88)	4.8 (0.19)	6.30 (13.90)	**BL200**	**1–200S**
	2 - 1/2	90.4 (3.56)	9.7 (0.38)	10.89 (24.00)	**BL250**	**1–250**
	3	108.0 (4.25)	9.7 (0.38)	14.51 (32.00)	**BL300**	**1–300**
	3 - 1/2	122.2 (4.81)	9.7 (0.38)	21.32 (47.00)	**BL350**	**1–350**
	4	138.2 (5.44)	9.7 (0.38)	27.22 (60.00)	**BL400**	**1–400**
	5	169.9 (6.69)	12.7 (0.50)	44.45 (98.00)	**BL500**	**1–500**
	6	201.7 (7.94)	12.7 (0.50)	72.57 (160.00)	**BL600**	**1–600**
PVC Gasketed Sealing Locknuts — Steel — Liquidtight						
	1/2	28.7 (1.13)	6.4 (0.25)	0.64 (1.40)	**BLSG50**	**SLG–50S**
	3/4	47.8 (1.88)	6.4 (0.25)	1.18 (2.60)	**BLSG75**	**SLG–75S**
	1	44.5 (1.75)	7.1 (0.28)	2.27 (5.00)	**BLSG100**	**SLG–100S**
	1-1/4	53.1 (2.09)	7.1 (0.28)	3.08 (6.80)	**BLSG125**	**SLG–125S**
	1-1/2	61.2 (2.41)	7.1 (0.28)	5.22 (11.50)	**BLSG150**	**SLG–150S**
	2	74.7 (2.94)	7.9 (0.31)	6.67 (14.70)	**BLSG200**	**SLG–200S**
	2 - 1/2	88.9 (3.50)	9.7 (0.38)	10.89 (24.00)	**BLSG250**	**SLG–250S**
	3	106.4 (4.19)	9.7 (0.38)	14.51 (32.00)	**BLSG300**	**SLG–300S**
	3 - 1/2	120.7 (4.75)	11.2 (0.44)	21.32 (47.00)	**BLSG350**	**SLG–350S**
	4	135.6 (5.34)	11.2 (0.44)	27.22 (60.00)	**BLSG400**	**SLG–400S** ①
	5	168.4 (6.63)	12.7 (0.50)	44.45 (98.00)	**BLSG500**	—
	6	200.2 (7.88)	14.2 (0.56)	72.57 (160.00)	**BLSG600**	—

① *Not UL or CSA certified*

Visit our website at **www.emerson.com** or contact us at **(800) 621-1506**.
© March 2018

EMERSON