

Eaton FCF70RN

Catalog Number: FCF70RN

Eaton Bussmann series FCF fuse, 70 A, 60 Hz, 50 Hz, 1 , CF, Black, Non-indicating, Electroless tin plated copper alloy terminal, Blade end|Class CF, 8 min at 200%, 200 kAIC at 600 V|50 kAIC at 600 Vdc, Glass filled PES, 600 V, 600 Vdc

General specifications

Product Name	Catalog Number
Eaton Bussmann series FCF fuse	FCF70RN
UPC	Product Length/Depth
051712362542	3.01 in
Product Height	Product Width
2.125 in	1 in
Product Weight	Warranty
0.284 lb	Not Applicable
Compliances	Certifications
CE Marked	UL Listed
RoHS Compliant	CSA Certified



Electrical rating

Amperage Rating

70 A

Frequency rating - max

60 Hz

Frequency rating - min

50 Hz

Interrupt rating

200 kAIC at 600 Vac

50 kAIC at 600 Vdc

Response time

8 min at 200%

Voltage rating

600 Vac, 600 Vdc

Physical details

Color

Black

Fuse type

Class CF

Fast acting

Material

Glass filled PES

Number of elements

1

Operating Temperature

-40° to 80°C

Packaging type

Standard

Terminal material

Electroless tin plated copper alloy terminal

General information

Class

Class CF

Connection

Blade end

Fuse indicator

Non-indicating

Special features

Superior overload and cycling capabilities

Used with

TCFH100N, CCP2-3-100CF

Resources

Catalogs

Bussmann series complete full line catalog no. 1007

FCF70RN~Fast Acting CUBEFuse 70A Non-indication

Multimedia

The Power of Space

Bussmann series Fuseology

Specifications and datasheets

Eaton Specification Sheet - FCF70RN



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)