


StreamLine® Modular Multifunctional Low Profile LED Status Indicator (SLM400/SLM450)

SPECIFICATIONS

Lamp Life:	50,000 Hours	
Light Source:	LED Array	
Operating Temperature:	-22°F to 122°F	-30°C to 50°C
Weight (unit(s) + base = total weight)		
SLM400 and SLM450	3.88 oz	0.11 kg
Shallow Base	2.12 oz	0.06 kg
Deep Base		
12-24 VAC/DC	4.23 oz	0.12 kg
120-240 VAC	6.0 oz	0.17 kg
Wall Mount		
12-24 VAC/DC	6.70 oz	0.19 kg
120-240 VAC	8.47 oz	0.24 kg
Pipe Mount		
12-24 VAC/DC	5.29 oz	0.15 kg
120-240 VAC	6.70 oz	0.19 kg
Twin Wall Mount		
12-24 VAC/DC	9.17 oz	0.26 kg
120-240 VAC	12.35 oz	0.35 kg

HOW TO ORDER

- Specify model number SLM400 and color for Opaque Lens or SLM450 and color for Fresnel Lens
- Specify required mounting base (see chart)
- Optional dome guard
For shallow mounting base (SLMDG0)
For deep mounting base (SLMDG1)
- Accessories for Twin and Wall Mount Bases
Cable Gland, M20, Gray, 2 Pack (K77700416)
Cable Gland, M20, Red, 2 Pack (K77700416-01)
- Accessories for Pipe Mount Base
1" NPT Adapter (SLMNPT1)
1/2" NPT Adapter (SLMNPT2)



MOUNTING BASE OPTIONS

	Shallow Base	Model Number	Base Color	Voltage	
		SLMBS-012-024GY	Gray	12-24VAC/DC	
	Deep Base	SLMBD-012-024GY	Gray	12-24VAC/DC	
		SLMBD-PNP-012-024GY	Gray	12-24VAC/DC	
		SLMBD-012-024R	Red	12-24VAC/DC	
		SLMBD-120-240GY	Gray	120-240VAC	
		SLMBD-120-240R	Red	120-240VAC	
	Wall Mount	SLMBW-012-024GY	Gray	12-24VAC/DC	
		SLMBW-PNP-012-024GY	Gray	12-24VAC/DC	
		SLMBW-120-240GY	Gray	120-240VAC	
	Pipe Mount	SLMBP-012-024GY	Gray	12-24VAC/DC	
		SLMBP-PNP-012-024GY	Gray	12-24VAC/DC	
		SLMBP-120-240GY	Gray	120-240VAC	
	Twin Wall Mount	SLMBT-012-024GY	Gray	12-24VAC/DC	
		SLMBT-PNP-012-024GY	Gray	12-24VAC/DC	
		SLMBT-120-240GY	Gray	120-240VAC	


StreamLine® Modular Multifunctional Low Profile LED Beacon (SLM300/SLM350)

SPECIFICATIONS






Lamp Life:	50,000 Hours	
Light Source:	LED Array	
Operating Temperature:	-22°F to 122°F	-30°C to 50°C
Weight (unit(s) + base = total weight)		
SLM300 and SLM350	3.88 oz	0.11 kg
Shallow Base	2.12 oz	0.06 kg
Deep Base		
12-24 VAC/DC	4.23 oz	0.12 kg
120-240 VAC	6.0 oz	0.17 kg
Wall Mount		
12-24 VAC/DC	6.70 oz	0.19 kg
120-240 VAC	8.47 oz	0.24 kg
Pipe Mount		
12-24 VAC/DC	5.29 oz	0.15 kg
120-240 VAC	6.70 oz	0.19 kg
Twin Wall Mount		
12-24 VAC/DC	9.17 oz	0.26 kg
120-240 VAC	12.35 oz	0.35 kg

HOW TO ORDER

- Specify model number SLM300 and color for Opaque Lens or SLM350 and color for Fresnel Lens
- Specify required mounting base (see chart)
- Optional dome guard
For shallow mounting base (SLMDG0)
For deep mounting base (SLMDG1)
- Accessories for Twin and Wall Mount Bases
Cable Gland, M20, Gray, 2 Pack (K77700416)
Cable Gland, M20, Red, 2 Pack (K77700416-01)
- Accessories for Pipe Mount Base
1" NPT Adapter (SLMNPT1)
1/2" NPT Adapter (SLMNPT2)



MOUNTING BASE OPTIONS

	Shallow Base	SLMBS-012-024GY	Gray	12-24VAC/DC	
	Deep Base	SLMBD-012-024GY	Gray	12-24VAC/DC	
		SLMBD-PNP-012-024GY	Gray	12-24VAC/DC	
		SLMBD-012-024R	Red	12-24VAC/DC	
		SLMBD-120-240GY	Gray	120-240VAC	
		SLMBD-120-240R	Red	120-240VAC	
	Wall Mount	SLMBW-012-024GY	Gray	12-24VAC/DC	
		SLMBW-PNP-012-024GY	Gray	12-24VAC/DC	
		SLMBW-120-240GY	Gray	120-240VAC	
	Pipe Mount	SLMBP-012-024GY	Gray	12-24VAC/DC	
		SLMBP-PNP-012-024GY	Gray	12-24VAC/DC	
		SLMBP-120-240GY	Gray	120-240VAC	
	Twin Wall Mount	SLMBT-012-024GY	Gray	12-24VAC/DC	
		SLMBT-PNP-012-024GY	Gray	12-24VAC/DC	
		SLMBT-120-240GY	Gray	120-240VAC	


StreamLine® Modular Multifunctional LED Combination Audible/Visual Signal (SLM600)

SPECIFICATIONS

Lamp Life:	50,000 Hours	
Light Source:	LED Array	
Operating Temperature:	-22°F to 122°F	-30°C to 50°C
Weight (unit(s) + base = total weight)		
SLM600	19.05 oz	0.54 kg
Shallow base	2.12 oz	0.06 kg
Deep Base		
12-24 VAC/DC	4.23 oz	0.12 kg
120-240 VAC	6.0 oz	0.17 kg
Wall Mount		
12-24 VAC/DC	6.70 oz	0.19 kg
120-240 VAC	8.47 oz	0.24 kg
Pipe Mount		
12-24 VAC/DC	5.29 oz	0.15 kg
120-240 VAC	6.70 oz	0.19 kg
Twin Wall Mount		
12-24 VAC/DC	9.17 oz	0.26 kg
120-240 VAC	12.35 oz	0.35 kg

HOW TO ORDER

- Specify model number SLM600 and color
- Specify required mounting base (see chart)
- Optional dome guard
For shallow mounting base (SLMDG2)
For deep mounting base (SLMDG3)
- Accessories for Twin and Wall Mount Bases
Cable Gland, M20, Gray, 2 Pack (K77700416)
Cable Gland, M20, Red, 2 Pack (K77700416-01)
- Accessories for Pipe Mount Base
1" NPT Adapter (SLMNPT1)
1/2" NPT Adapter (SLMNPT2)



MOUNTING BASE OPTIONS

	Shallow Base	Model Number	Base Color	Voltage	
		SLMBS-012-024GY	Gray	12-24VAC/DC	
	Deep Base	SLMBD-012-024GY	Gray	12-24VAC/DC	
		SLMBD-PNP-012-024GY	Gray	12-24VAC/DC	
		SLMBD-012-024R	Red	12-24VAC/DC	
		SLMBD-120-240GY	Gray	120-240VAC	
		SLMBD-120-240R	Red	120-240VAC	
	Wall Mount	SLMBW-012-024GY	Gray	12-24VAC/DC	
		SLMBW-PNP-012-024GY	Gray	12-24VAC/DC	
		SLMBW-120-240GY	Gray	120-240VAC	
	Pipe Mount	SLMBP-012-024GY	Gray	12-24VAC/DC	
		SLMBP-PNP-012-024GY	Gray	12-24VAC/DC	
		SLMBP-120-240GY	Gray	120-240VAC	
	Twin Wall Mount	SLMBT-012-024GY	Gray	12-24VAC/DC	
		SLMBT-PNP-012-024GY	Gray	12-24VAC/DC	
		SLMBT-120-240GY	Gray	120-240VAC	

StreamLine® Modular Electronic Sounder (SLM700)

S P E C I F I C A T I O N S


Operating Temperature: -22°F to 122°F -30°C to 50°C

Weight (unit(s) + base = total weight)

SLM700	7.76 oz	0.22 kg
Shallow Base	2.12 oz	0.06 kg
Deep Base		
12-24VAC/DC	4.23 oz	0.12 kg
120-240VAC	6.0 oz	0.17 kg
Wall Mount		
12-24VAC/DC	6.70 oz	0.19 kg
120-240VAC	8.47 oz	0.24 kg
Pipe Mount		
12-24VAC/DC	5.29 oz	0.15 kg
120-240VAC	6.70 oz	0.19 kg
Twin Wall Mount		
12-24 VAC/DC	9.17 oz	0.26 kg
120-240 VAC	12.35 oz	0.35 kg

H O W T O O R D E R

- Specify model number:
SLM700GY – Gray body
SLM700R – Red body
- Specify required mounting base (see chart)
- Optional dome guard
SLMDG1 – For shallow mounting base
SLMDG2 – For deep mounting base
- Accessories for Twin and Wall Mount Bases
K77700416 – Cable Gland, M20, Gray, 2 Pack
K77700416-01 – Cable Gland, M20, Red, 2 Pack
- Accessories for Pipe Mount Base
SLMNPT1 – 1" NPT Adapter
SLMNPT2 – 1/2" NPT Adapter



M O U N T I N G B A S E O P T I O N S

	Shallow Base	Model Number	Base Color	Voltage	
		SLMBS-012-024GY	Gray	12-24VAC/DC	
	Deep Base	SLMBD-012-024GY	Gray	12-24VAC/DC	
		SLMBD-PNP-012-024GY	Gray	12-24VAC/DC	
		SLMBD-012-024R	Red	12-24VAC/DC	
		SLMBD-120-240GY	Gray	120-240VAC	
		SLMBD-120-240R	Red	120-240VAC	
	Wall Mount	SLMBW-012-024GY	Gray	12-24VAC/DC	
		SLMBW-PNP-012-024GY	Gray	12-24VAC/DC	
		SLMBW-120-240GY	Gray	120-240VAC	
	Pipe Mount	SLMBP-012-024GY	Gray	12-24VAC/DC	
		SLMBP-PNP-012-024GY	Gray	12-24VAC/DC	
		SLMBP-120-240GY	Gray	120-240VAC	
	Twin Wall Mount	SLMBT-012-024GY	Gray	12-24VAC/DC	
		SLMBT-PNP-012-024GY	Gray	12-24VAC/DC	
		SLMBT-120-240GY	Gray	120-240VAC	