



GREENLEE®

A Textron Company

CS-8000 **Circuit Seeker™ Circuit Tracer**



There With You™
faster • safer • easier®

Specifications

Operating Conditions:

Temperature: 0 to +50 °C (32 to 122 °F)

Altitude: 2000 m (6500') maximum

Pollution Degree: 2

Indoor use only

Transmitter

Measurement Category: Category III, 750V

Operating Voltage: 0-750 V AC/DC

Live line LED indicates voltage above 12 VAC or 5 VDC

Frequency: 15.15 kHz

Low battery indicator

Batteries: Two AA batteries (NEDA 15A or IEC LR6)

Receiver

Range from Receiver to item with Signal:

Live Line Mode – up to 20 ft (6 m) from circuit

Open Line Mode – Up to 10 ft. (3 m) with a metallic connection to ground.
1 to 3 ft. (.3 to .9 m) with a capacitive ground reference.

Low battery indicator

Batteries: Two AA batteries (NEDA 15A or IEC LR6)

Ordering Information

Catalog #	UPC #	Description	QTY
CS-8000	12126	Seeker, Circuit	1
12849	12849 R	Transmitter	1
12850	12850 R	Receiver	1
10057	10057 R	(2) Alligator Clips	1
10054	10054 R	AC Blade	1
12852	12852 R	AC Plug Adapter	1
12853	12853 R	(2) Extension Leads	1
12851	12851 R	Carrying Case	1

R = REPLACEMENT PART



www.greenlee.com • MA-5366 2/09

4455 Boeing Drive • Rockford, IL 61109-2988 • USA • 815-397-7070

©2009 Greenlee Textron Inc. • Printed in USA

Greenlee Textron Inc. is a subsidiary of Textron Inc.