



Number of contacts

4+



80 A 830 V 8 kV 3

Han-Com	Identification	Conductor cross-section (mm²)	Part number		Drawing (dimensions in mm)																								
			Male	Female																									
	Han-Com® , Screw termination, Contact surface: Silver plated 	1,5 ... 16	09 38 006 2611	09 38 006 2711	 1) distance for contact max. 21 mm  Contact arrangement (view from termination side) <table><tr><th colspan="3">power contacts</th></tr><tr><th>wire gauge</th><th>tightening torque</th><th>stripping length</th></tr><tr><td>1.5 mm²</td><td>1.2 Nm</td><td>14 mm</td></tr><tr><td>2.5 mm²</td><td>2 Nm</td><td>14 mm</td></tr><tr><td>4 mm²</td><td>3 Nm</td><td>14 mm</td></tr><tr><td>6 mm²</td><td>3 Nm</td><td>14 mm</td></tr><tr><td>10 mm²</td><td>3 Nm</td><td>14 mm</td></tr><tr><td>16 mm²</td><td>3 Nm</td><td>14 mm</td></tr></table>	power contacts			wire gauge	tightening torque	stripping length	1.5 mm²	1.2 Nm	14 mm	2.5 mm²	2 Nm	14 mm	4 mm²	3 Nm	14 mm	6 mm²	3 Nm	14 mm	10 mm²	3 Nm	14 mm	16 mm²	3 Nm	14 mm
power contacts																													
wire gauge	tightening torque	stripping length																											
1.5 mm²	1.2 Nm	14 mm																											
2.5 mm²	2 Nm	14 mm																											
4 mm²	3 Nm	14 mm																											
6 mm²	3 Nm	14 mm																											
10 mm²	3 Nm	14 mm																											
16 mm²	3 Nm	14 mm																											